



STAINLESS STEEL
HAND SINKS
KNEE VALVE



Item #: _____ **Qty #:** _____
Model #: _____
Project #: _____



7-PS-62

SPACE SAVER



7-PS-63

See page A-7 for more
 Space Saver Units



7-PS-30

Keyhole Bracket for
 easier installation
 and greater stability.



7-PS-82

FEATURES:

One piece **Deep Drawn** sink bowl design.
7-PS-30 Sink bowl is 16" x 14" x 6".
7-PS-62 & 7-PS-82 Sink bowl is 10" x 14" x 5".
7-PS-63 Sink bowl is 9" x 9" x 5".
 Keyhole wall mount bracket.
 Stainless steel basket drain 1-1/2" IPS.
 Knee valve operated faucet provides true hands-free operation.
 All sink bowls have a large liberal radii with a minimum dimension of 2" and are rectangular in design for increased capacity.
 Apron conceals plumbing on all three sides.
 "Hands Free" splash mounted gooseneck faucet furnished with aerator.

Specific Features:

7-PS-82 has Towel Dispenser with hinged towel box. Unit uses standard C-fold towels. Liquid soap dispenser also included.
7-PS-63 "Hands Free" splash mounted 6" "D" Spout faucet furnished with aerator.

CONSTRUCTION:

All TIG welded.
 Welded areas blended to match adjacent surfaces and to a satin finish.
 Die formed Countertop Edge with a 3/8" No-Drip offset.
 One sheet of stainless steel - No Seams.

MATERIAL:

Heavy gauge type 304 series stainless steel.
 Wall mounting bracket is galvanized steel and of offset design.
 All fittings are brass / chrome plated unless otherwise indicated.

MECHANICAL:

Faucet supply is 1/2" IPS male thread hot and cold.
 Knee Valve is barrel type and is activated by pedal.
 (Contractor on site must connect faucet to knee operated valves.)

Standard Faucet conforms to NSF 61 Standard 9. An optional faucet upgrade is required for compliance to AB 1953 Standards.

For Replacement Faucets & Upgrades, Drains & Accessories visit our website at www.advancetabco.com



Customer Service Available To Assist You 1-800-645-3166 8:30 am - 8:00 pm E.S.T.
 Email Orders To: customer@advancetabco.com. For Smart Fabrication™ Quotes, Email To: smartfab@advancetabco.com or Fax To: 631-586-2933

NEW YORK
 Fax: (631) 242-6900

GEORGIA
 Fax: (770) 775-5625

TEXAS
 Fax: (972) 932-4795

NEVADA
 Fax: (775) 972-1578

DIMENSIONS and SPECIFICATIONS

TOL Overall: ± .500" Interior: ± .250"

FITTINGS SUPPLIED AS SHOWN

ALL DIMENSIONS ARE TYPICAL

<p>7-PS-62</p> <p>25 lbs.</p>	<p>7-PS-82</p> <p>38 lbs.</p>
<p>7-PS-30</p> <p>33 lbs.</p>	<p>7-PS-63</p> <p>20 lbs.</p>

KNEE VALVE DETAIL

