



STAINLESS STEEL  
**HAND SINKS**  
**KNEE VALVE**



**Item #:** \_\_\_\_\_ **Qty #:** \_\_\_\_\_  
**Model #:** \_\_\_\_\_  
**Project #:** \_\_\_\_\_



7-PS-62

**SPACE SAVER**



7-PS-63

See page A-7 for more  
 Space Saver Units



7-PS-30

Keyhole Bracket for  
 easier installation  
 and greater stability.



7-PS-82

**FEATURES:**

- One piece **Deep Drawn** sink bowl design.
  - 7-PS-30** Sink bowl is 16" x 14" x 6".
  - 7-PS-62 & 7-PS-82** Sink bowl is 10" x 14" x 5".
  - 7-PS-63** Sink bowl is 9" x 9" x 5".
  - Keyhole wall mount bracket.
  - Stainless steel basket drain 1-1/2" IPS.
  - Knee valve operated faucet provides true hands-free operation.
  - All sink bowls have a large liberal radii with a minimum dimension of 2" and are rectangular in design for increased capacity.
  - Apron conceals plumbing on all three sides.
  - "Hands Free" splash mounted gooseneck faucet furnished with aerator.
- Specific Features:**
- 7-PS-82** has Towel Dispenser with hinged towel box. Unit uses standard C-fold towels. Liquid soap dispenser also included.
  - 7-PS-63** "Hands Free" splash mounted 6" "D" Spout faucet furnished with aerator.

**CONSTRUCTION:**

- All TIG welded.
- Welded areas blended to match adjacent surfaces and to a satin finish.
- Die formed Countertop Edge with a 3/8" No-Drip offset.
- One sheet of stainless steel - No Seams.

**MATERIAL:**

- Heavy gauge type 304 series stainless steel.
- Wall mounting bracket is galvanized steel and of offset design.
- All fittings are brass / chrome plated unless otherwise indicated.

**MECHANICAL:**

- Faucet supply is 1/2" IPS male thread hot and cold.
- Knee Valve is barrel type and is activated by pedal.
- (Contractor on site must connect faucet to knee operated valves.)

**Standard Faucet conforms to NSF 61 Standard 9. An optional faucet upgrade is required for compliance to AB 1953 Standards.**

For Replacement Faucets & Upgrades, Drains & Accessories visit our website at [www.advancetabco.com](http://www.advancetabco.com)

<p>www.advancetabco.com</p>	<p><b>Customer Service Available To Assist You 1-800-645-3166 8:30 am - 8:00 pm E.S.T.</b></p> <p>Email Orders To: <a href="mailto:customer@advancetabco.com">customer@advancetabco.com</a>. For Smart Fabrication™ Quotes, Email To: <a href="mailto:smartfab@advancetabco.com">smartfab@advancetabco.com</a> or Fax To: 631-586-2933</p>			
	<p><b>NEW YORK</b>          Fax: (631) 242-6900</p>	<p><b>GEORGIA</b>          Fax: (770) 775-5625</p>	<p><b>TEXAS</b>          Fax: (972) 932-4795</p>	<p><b>NEVADA</b>          Fax: (775) 972-1578</p>

# DIMENSIONS and SPECIFICATIONS

TOL Overall: ± .500" Interior: ± .250"

FITTINGS SUPPLIED AS SHOWN

ALL DIMENSIONS ARE TYPICAL

<p><b>7-PS-62</b></p> <p><b>25 lbs.</b></p>	<p><b>7-PS-82</b></p> <p><b>38 lbs.</b></p>
<p><b>7-PS-30</b></p> <p><b>33 lbs.</b></p>	<p><b>7-PS-63</b></p> <p><b>20 lbs.</b></p>

### KNEE VALVE DETAIL

**1/2" IPS FEMALE**

