

JOB _____ ITEM # _____ QTY # _____



MODEL 2AT-ST

CABINET STYLE, MOBILE, ADJUSTABLE
 SERIES AT-ST (UNHEATED)
 SERIES AT-STH (HEATED)
 SERIES AT-STH-XH (HEATED HIGH HEAT)

SPECIFICATIONS

Series AT-ST unheated, AT-STH heated, and AT-STH-XH High Heated, cabinet style, mobile dish dispensers.

CABINET

The body and top are of unibody design, constructed of heavy gauge stainless steel panels formed to provide rigidity. Heated models (AT-STH) are insulated on sides and top and lined with steel panels.

DISPENSERS

All units are fitted with model AT adjustable drop-in dish dispensers (see catalog page D-9 for specifications).

CAPACITIES

The capacity of each model AT dispenser is approximately 28 to 36 bowls or 50 to 72 plates.

HEATING SYSTEM

AT-STH models are fitted with a 120 or 208 volt (as specified) single phase, thermostatically controlled heating system complete with a recessed control panel with on-off switch, neon pilot light and adjustable thermostat. The unit is equipped with a 4' long, three wire cord set with NEMA 5-15P plug for 120V or NEMA 6-15P plug for 208 volt.

MODEL NUMBER

- 2AT-ST 2AT-STH
- 3AT-ST 3AT-STH
- 4AT-ST 4AT-STH

SERIES AT-STH-XH (PLATTERS)

SERIES AT-STH-XH are heated, cabinet style, mobile plate or platter dispensers. They are fitted with a high wattage, forced air heating system for use when plates or platters need to be brought to a higher temperature than usual.

CAPACITIES

The capacity of each model AT dispenser is approximately 28 to 36 bowls or 50 to 72 plates. The capacity of each model ATO dispenser is approximately 50 to 72 platters.

HEATING SYSTEM

The unit is heated by a forced air heating system designed for rapid and even heating. A recessed control panel is fitted with an on-off switch, a neon pilot light and an adjustable thermostat. The system is rated 120 volt, single phase, 1500 Watts; and draws 12.5 Amps. A 4' long, three wire cord set with NEMA 5-15P plug is included.

CASTERS

The cabinet is mounted on four 4" diameter heavy duty, swivel casters.

OPTIONS

- WB - Two locking casters
- PB - Perimeter Bumper
- B - Corner Bumper
- V - Vertical Bumper
- Y4 - Polyurethane 4" casters (set of 4)
- Y5 - Polyurethane 5" casters (set of 4)
- SSTC - Stainless Steel Tube Covers
- XH - High Heat (1500 Watt Element)

SPEC E-19


PIPER PRODUCTS
 BUILT TO LAST
www.piperonline.net

300 S. 84th Avenue
 Wausau, WI 54401
 Phone: 800-544-3057
 Fax: 715-842-3125


NOTE: Please circle model number required

| UNHEATED MODELS | | | | | | | | | |
|--------------------|-----------|--------|--------|-----------|--------|--------|-----------|--------|--------|
| DISH DIAM. | MODEL NO. | W | L | MODEL NO. | W | L | MODEL NO. | W | L |
| . 5-1/8 Max. | 2AT1-ST | 18-1/8 | 28-1/8 | 3AT1-ST | 18-1/8 | 28-1/8 | 4AT1-ST | 22-5/8 | 28-1/8 |
| . 5-1/4 to 5-7/8 | 2AT2-ST | 18-1/8 | 28-1/8 | 3AT2-ST | 18-1/8 | 28-1/8 | 4AT2-ST | 22-5/8 | 28-1/8 |
| . 6 to 6-5/8 | 2AT3-ST | 18-1/8 | 28-1/8 | 3AT3-ST | 26-1/8 | 28-1/8 | 4AT3-ST | 22-5/8 | 28-1/8 |
| . 6-3/4 to 7-3/8 | 2AT4-ST | 18-1/8 | 28-1/8 | 3AT4-ST | 26-1/8 | 28-1/8 | 4AT4-ST | 31-3/8 | 33-1/8 |
| . 7-1/2 to 8-1/4 | 2AT5-ST | 18-1/8 | 28-1/8 | 3AT5-ST | 26-1/8 | 28-1/8 | 4AT5-ST | 31-3/8 | 33-1/8 |
| . 8-3/8 to 9-1/4 | 2AT6-ST | 20-1/8 | 35-1/8 | 3AT6-ST | 31-3/8 | 33-1/8 | 4AT6-ST | 31-3/8 | 33-1/8 |
| . 9-1/8 to 10-1/4 | 2AT7-ST | 20-1/8 | 35-1/8 | 3AT7-ST | 31-3/8 | 33-1/8 | 4AT7-ST | 31-3/8 | 33-1/8 |
| . 10-3/8 to 11-1/4 | 2AT75-ST | 20-1/8 | 35-1/8 | 3AT75-ST | 31-3/8 | 33-1/8 | 4AT75-ST | 31-3/8 | 33-1/8 |
| . 11-3/8 to 12 | 2AT8-ST | 20-1/8 | 35-1/8 | 3AT8-ST | 31-3/8 | 33-1/8 | N/A | | |
| Shipping Wt. | 140 | | | 175 | | | 200 | | |


| | MODEL NO. | W | L | MODEL NO. | W | L | MODEL NO. | W | L |
|--------------------|---------------|--------|--------|----------------|--------|--------|----------------|--------|--------|
| . 5-1/8 Max. | 2AT1-STH | 18-1/8 | 28-1/8 | 3AT1-STH | 18-1/8 | 28-1/8 | 4AT1-STH | 22-5/8 | 28-1/8 |
| . 5-1/4 to 5-7/8 | 2AT2-STH | 18-1/8 | 28-1/8 | 3AT2-STH | 18-1/8 | 28-1/8 | 4AT2-STH | 22-5/8 | 28-1/8 |
| . 6 to 6-5/8 | 2AT3-STH | 18-1/8 | 28-1/8 | 3AT3-STH | 26-1/8 | 28-1/8 | 4AT3-STH | 22-5/8 | 28-1/8 |
| . 6-3/4 to 7-3/8 | 2AT4-STH | 18-1/8 | 28-1/8 | 3AT4-STH | 26-1/8 | 28-1/8 | 4AT4-STH | 31-3/8 | 33-1/8 |
| . 7-1/2 to 8-1/4 | 2AT5-STH | 18-1/8 | 28-1/8 | 3AT5-STH | 26-1/8 | 28-1/8 | 4AT5-STH | 31-3/8 | 33-1/8 |
| . 8-3/8 to 9-1/4 | 2AT6-STH | 20-1/8 | 35-1/8 | 3AT6-STH | 31-3/8 | 33-1/8 | 4AT6-STH | 31-3/8 | 33-1/8 |
| . 9-1/8 to 10-1/4 | 2AT7-STH | 20-1/8 | 35-1/8 | 3AT7-STH | 31-3/8 | 33-1/8 | 4AT7-STH | 31-3/8 | 33-1/8 |
| . 10-3/8 to 11-1/4 | 2AT75-STH | 20-1/8 | 35-1/8 | 3AT75-STH | 31-3/8 | 33-1/8 | 4AT75-STH | 31-3/8 | 33-1/8 |
| . 11-3/8 to 12 | 2AT8-STH | 20-1/8 | 35-1/8 | 3AT8-STH | 31-3/8 | 33-1/8 | N/A | | |
| Shipping Wt. | 175 | | | 225 | | | 275 | | |
| Watts | 750 (XH 1500) | | | 1500 (XH 3000) | | | 1500 (XH 3000) | | |
| Amps. @ 120V | 6.3 (XH 12.5) | | | 12.5 (XH 25) | | | 12.5 (XH 25) | | |



MODEL 2AT-ST(H)



MODEL 3AT-ST(H)



MODEL 4AT-ST(H)

Height - Cabinets 36"
Overall height (including dish guides) add 4"

E-19 SPEC

PIPER PRODUCTS
BUILT TO LAST
www.piperonline.net

300 S. 84th Avenue
Wausau, WI 54401
Phone: 800-544-3057
Fax: 715-842-3125

LIMITED WARRANTY: PIPER PRODUCTS warrants to the original purchaser parts and labor for a period of twelve (12) months from the date of purchase. See manufacturer's complete warranty for details.

It is our policy to build equipment which is design certified by companies that have been accredited at the Federal Level by the Occupational Safety and Health Agency (OSHA) and ANSI as a National Recognized Testing Laboratory. These companies include CSA International, Underwriters Laboratories, and the National Sanitation Foundation. However, a continuing program of product improvement makes it necessary to submit new models to the agencies as they are developed. Consequently, all models may not bear the appropriate labels at all times.

We reserve the right to change specifications and product design without notice. Such revisions do not entitle buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Information is not for design purposes.