



TANKLESS ELECTRIC WATER HEATER FOR HAND SINKS 7-PS-92

FEATURES:

Unlimited supply of hot water (No water storage tank required)
 Only 1 single supply line of cold water is required to feed the unit.
 Single shut off valve for ease of service.
 Scald Guard Technology keeps water temperature within safe limits at all times.
 Includes Fittings and Supply Lines for Faucet

SPECIFICATIONS:

ETL listed (water heater only).
 120 volts / single phase / Must Be Hard Wired.
 Wattage 3.0 kw.
 Amps =25 (Required circuit breaker size: 30 amps).
 Electrical Connection to Circuit Breaker Panel Box By Others.
 Max. water pressure = 150 psi.
 Gallons per minute= 0.5
 Temperature rise @ 0.5 gpm = 41 degrees.

IMPORTANT NOTES:

Must Specify Hand Sink Model When Ordering to ensure proper fittings and faucet supply lines.
 Depending on incoming water pressure, it may be required to adjust the cold water Inlet Valve to acheive the temperature required.

ADDITIONAL NOTES FOR FOOT & KNEE VALVE HAND SINKS:

Factory Installed Only in Pedestal Base Units.
 If desired temperature is not reached, adjust the hot water Mixing Valve that is on the Foot or Knee Pedal.

Item #: _____ *Qty #:* _____
Model #: _____
Project #: _____

**Only 1 single supply line of cold water is required to feed the unit.
 (Supply: 1/2" NPT Male)**



**Heater Shown installed with a Hand Sink
 (Sink sold seperately)**



**Heater Shown installed in a Pedestal
 Base Unit
 (Sink sold seperately. Must be
 Factory Installed)**



**Heater feeds hot and cold water supply
 to the Valve in Pedestal Base and
 Knee Valve Units
 (Pedal Valve Shown)**



Customer Service Available To Assist You 1-800-645-3166 8:30 am - 8:00 pm E.S.T.
 Email Orders To: customer@advancetabco.com. For Smart Fabrication™ Quotes, Email To: smartfab@advancetabco.com or Fax To: 631-586-2933

NEW YORK
 Fax: (631) 242-6900

GEORGIA
 Fax: (770) 775-5625

TEXAS
 Fax: (972) 932-4795

NEVADA
 Fax: (775) 972-1578