

## ELECTRIC TABLES WITH UNDERSHELF





ltem #:	Qty #:	
Model #:		
Proiect #:		

HF-2E-120 Shown

#### **FEATURES:**

Stainless steel undershelf

Fiberglass insulation between each compartment Units intended for dry use. For hot water bath, must use optional Spillage Pans # **SP-A** (Aluminum) or # **SP-S** (Stainless)

1" thick poly cutting board (8" wide)

#### For Mobile Units:

**SU-25** - 5" swivel casters, two with brakes Universal mount push handle (right/left) on mobile units

#### **MATERIAL:**

TOP: 20 gauge #302 stainless steel with die stamped pan openings. (11.875" x 20.062") BODY: 22 gauge #430 stainless steel LEGS: 18 gauge stainless steel with fully adjustable non-marking tip bullet foot UNDERSHELF: 22 gauge #430 stainless steel LINERS: 8" deep, 22 Gauge galvanized or #302 stainless steel

CUTTING BOARD: White thermoplastic CUTTING BOARD BRACKETS: 16 gauge, #302 stainless steel

### **ELECTRICAL:**

120V units yield 500 Watts 208V/240V dual voltage units yield 750 Watts at 208V and 1000 Watts at 240V 6' electrical cord with plug Infinite control knobs Indicator lights



GALVANIZED LINERS	STAINLESS STEEL LINERS	Length	# of Wells	Weight	Cubic Feet	Volts	NEMA Plug	Power Consumption
HF-2E-120	HF-2E-120-SS	A = 31-13/16"	2	92	28	120	5-20P	15/500
HF-3E-120	HF-3E-120-SS	B = 47-1/8"	3	120	41	120	5-20P	15/500
HF-4E-120	HF-4E-120-SS	C = 62-7/16"	4	152	54	120	L5-30P	30/500
HF-2E-240	HF-2E-240-SS	A = 31-13/16"	2	92	28	208/240	6-20P	15/750 • 20/1000
HF-3E-240	HF-3E-240-SS	B = 47-1/8"	3	120	41	208/240	6-20P	15/750 • 20/1000
HF-4E-240	HF-4E-240-SS	C = 62-7/16"	4	152	54	208/240	L6-30P	20/750 • 30/1000
HF-5E-240	HF-5E-240-SS	D = 77-3/4"	5	170	67	208/240	L6-30P	20/750 • 30/1000

NOTE: Units are not designed to cook or heat frozen or refrigerated foods. Food placed in tables should already be hot, and the table will maintain the proper temperatures









<u>up</u> <u>Nema P</u>

NEMA PLUG L6-30P



Customer Service Available To Assist You 1-800-645-3166 8:30 am - 8:00 pm E.S.T.

For Orders & Customer Service: Email: customer@advancetabco.com or Fax: 631-242-6900 For Smart Fabrication™ Quotes: Email: smartfab@advancetabco.com or Fax: 631-586-2933

# **DIMENSIONS and SPECIFICATIONS**

TOL ± .125"

ALL DIMENSIONS ARE TYPICAL



