



All Stainless Steel Uni-Serv Speed Bars

19" and 24" Wide Units - Deep Drawn Bowls

Item #:	Qty #:
Model #: _	
Project #:	



Featuring Deep Drawn Seamless Bowls



MECHANICAL:

Includes 4" O.C. splash mount gooseneck spout faucet*.

Faucet meet federal lead free standards.

1" IPS drain (non-cold plate ice bin and glassware shelf). 1/2" IPS drain (cold plate ice bin).

3 1/2" basket drain (sink bowl).

FEATURES:

One piece **Deep Drawn** dump sink measuring 9 1/2" x 11 1/2" x 6". 30"x 11" insulated ice bin on either left or right side.

30" wide speed rail.

Drop down glassware storage shelf.

Blender recess station.

Two injection molded plastic bottle racks.

Optional 10-circuit cold plate sealed into bottom of ice bin.

7" backsplash.

Stainless steel legs with adjustable stainless steel bullet feet.

MATERIAL:

20 gauge, 300 stainless steel

Recessed Glassware Shelf: 18 gauge, 300 stainless steel **Legs:** 1 5/8" O.D. 14 gauge, stainless steel with adjustable

stainless steel bullet feet

Ice Bin Insulation: 2 lbs. density foam-in-place

Cold Plate: Cast aluminum with 10 circuits (8 syrup and 2 water lines)

with 5/16" diameter stainless steel bump and swedge ends.

OPTIONAL:

K-316-LU - Add wrist handles

19" WIDE Model #	Approx. Weight	Approx. Cu. Ft.	24" WIDE Model #	Approx. Weight	Approx. Cu. Ft.	Distance To Drain (A)	Distance To Drain (B)	Distance To Drain (C)	Ice Bin Capacity	Ice Bin Location
PRU-19-60L	130 lbs.	23	PRU-24-60L	135 lbs.	26	15"	38"	57"	89 lbs.	Left
PRU-19-60R	130 lbs.	23	PRU-24-60R	135 lbs.	26	15"	38"	57"	89 lbs.	Right
With 10-Circ	1	 I	1	170 11	00	l 45"	00"		00 lb -	
PRU-19-60L-10	165 lbs.	23	PRU-24-60L-10	170 lbs.	26	15"	38"	57"	89 lbs.	Left
PRU-19-60R-10	165 lbs.	23	PRU-24-60R-10	170 lbs.	26	15"	38"	57"	89 lbs.	Right



Customer Service Available To Assist You 1-800-645-3166 8:30 am - 8:00 pm E.S.T.

For Orders & Customer Service:

Email: customer@advancetabco.com or Fax: 631-242-6900

For Smart Fabrication™ Quotes:

Email: smartfab@advancetabco.com or Fax: 631-586-2933

DIMENSIONS and SPECIFICATIONS

TOL Overall: ± .500" Interior: ± .250"

ALL DIMENSIONS ARE TYPICAL

PRU-19 Series PRU-24 Series

