Item No.

Individual Thermostatically Controlled Burners Every 12 Inches Maintain Consistent Temperatures Under Heavy Load Conditions. Precise thermostats and exclusive plate temperature sensors which respond to temperature fluctuations quickly, allow separate heat zones for different products.

Introducing A First Of Its Kind, A Full-Depth Side **Grease Drawer.** Grilling requires constant scraping between loads. Now the Anets GoldenGrill line of grills has a feature to make this task quicker and easier, saving time and money. A simple scrape to the side and the grill byproduct is disposed in the drawer. Open access to the drawer along the entire cooking depth of the grill makes it quick and convenient.

STANDARD FEATURES

- High nickel content 3/4" precision ground hot rolled steel plate
- One burner per foot: 30,000 BTUH per burner (24" models) 40,000 BTUH per burner (30" models)
- Stainless steel front, sides and splashguards
- Snap action thermostats every 12 inches, (1 per burner)
- Spark ignitor for lighting pilots
- Double wall construction keeps the operator and kitchen cool

SIDE GREASE DRAWER FEATURES

- Full grill depth access to drawer
- Drawer is all stainless steel
- Easy to remove and clean, dishwasher
- Built in spatula holder
- Drawer easily slides in and out on a solid frame with guides



SG24X48-LD shown on optional stainless steel stand with undershelf and casters











SG-LD Models

Golden GRILL

SPECIFICATIONS

- Model
- Certification
- BTUH input
- Gas Pressure
- Gas Connection
- Electrical
- Plate
- Burners
- Thermostats
- Temperature Range
- Safety Pilots
- Spark ignitor
- Cabinet

SG-LD Models (See chart below)

ETL, CETL, NSF

30,000 per burner (foot), 24" Deep Models 40,000 per burner (foot), 30" Deep Models

NG 3.5" WC, LP 10" WC, Pressure regulator included

3/4" NPT

None

High nickel content 3/4" precision ground hot rolled steel plate

Aluminized steel


Gas operated, snap action

200-550F (93-288C)


100% gas shut-off valve

Piezo electric


Front and sides, stainless steel Splashguard, stainless steel



Top View



Side View



Front View

STANDARD ACCESSORIES

- Stainless steel sides
- Safety pilots
- Spark ignitor
- Pressure regulator
- 4" Adjustable chrome plated legs

OPTIONS AND ACCESSORIES

- Removable cutting board bracket assembly
- Stainless steel stands
- 11" High backsplash

DIMENSIONS

24" LD MODELS

0	SG	SG	SG	SG	SG
Overall	24X24	24X36	24X48	24X60	24X72
(W) Width	27.25"	39.25"	51.25"	63.25"	75.25"
Height	15.25"	15.25"	15.25"	15.25"	15.25"
Depth	29.75"	29.75"	29.75"	29.75"	29.75"
Plate					
Width	24"	36"	48"	60"	72"
(Depth)	24"	24"	24"	24"	24"
NG BTUH	60,000	90,000	120,000	150,000	180,000
LP BTUH	60000	90,000	120,000	150,000	180,000

Specifications subject to change without notice. SS# 222 Revised 10/01

Printed in the U.S.A.

30" LD MODELS

Overall	SG 30X24	SG 30X36	SG 30X48	SG 30X60	SG 30X72	1
(W) Width	27.25"	39.25"	51.25"	63.25"	75.25"	
Height	15.25"	15.25"	15.25"	15.25"	15.25"	
Depth	35.75"	35.75"	35.75"	35.75"	35.75"	
Plate						
Width	24"	36"	48"	60"	72"	
Depth	30"	30"	30″	30"	30"	
NG BTUH	80,000	120,000	160,000	200,000	240,000	
LP BTUH	72,000	108,000	144,000	180,000	216,000	