

**COMBITHERM®**  
**CTC20-20E**  
**ELECTRIC BOILER-FREE**



**CAPACITY**

- Twenty (20) full-size sheet pans; twenty (20) GN 2/1 pans; forty (40) full-size hotel or GN 1/1 pans; two rows deep
- Roll-in pan cart with twenty (20) non-tilt support rails; 13" (330mm) horizontal width between rails, 2-9/16" (65mm) vertical spacing between rails

**CONSTRUCTION**

- Stainless steel exterior, bright annealed interior
- Seamless welded interior stainless steel cavity
- CoolTouch3™ triple pane window door with hinged inner glass prevents additional heat loss and increases cooking efficiency
- Door is hinged right with a 130° swing
- High efficiency LED lighting integrated in the door
- Hands free positive catch door handle with lighted visual alerts [PATENT PENDING]
- PROrinse™ ergonomic retractable hand shower includes a safety shutoff interlock that shuts off water to the hose [PATENT PENDING] and a built-in back flow preventer
- SafeVent™ provides automatic steam venting at the end of the cooking cycle [PATENT #7,282,674]
- Zero Clearance system maximizes floor space utilization with features that carefully protect temperature sensitive components and controls [PATENT PENDING]
- Adjustable stainless steel flanged legs provide stability
- Roll-in pan cart includes mounted drip tray and four (4) swivel casters, including two (2) with brakes

**CT CLASSIC™ STANDARD FEATURES**

- Oven with state-of-the-art innovative solutions that meld together perfectly to deliver high performance standards, consistent food quality, and production efficiency.
- Classic control provides a simple and intuitive push button operation that commands all the oven functions with icons that are easy to identify.

- LED display indicates cooking mode, temperature settings, time remaining, and various instructions.
- Three cooking modes:  
 Steam - 85°F to 250°F (30°C to 120°C)  
 Convection - 85°F to 575°F (30°C to 300°C)  
 Combination - 212°F to 575°F (100°C to 300°C)
- Cook time is displayed in hours : minutes.

- Two different fan speeds expands cooking capabilities for products affected by a high velocity of air movement.
- Cool down feature provides the operator with the ability to lower the temperature of the oven compartment at an accelerated pace.
- CombiClean® fully automated cleaning with one heavy-duty cleaning cycle.

**SHORT FORM SPEC**

Provide Alto-Shaam Combitherm® CT Classic™ floor-standing model CTC20-20E boiler-free electric CombiOven designed with EcoSmart® technology for reduced energy and water consumption. Includes operational modes for steam, convection, and a combination of steam and convection heat. Oven is to be constructed of 18 gauge stainless steel interior cavity. Oven includes an attached retractable hand shower spray hose with safety shutoff interlock system and a back flow preventer. Classic control includes a

cool-down function, automatic cleaning function, fan with two (2) speeds. Oven includes standard right-hand door hinging with integrated preheat strip and six (6) adjustable stainless steel legs. Roll-in pan cart accommodates up to twenty (20) full-size sheet pans, twenty (20) GN 2/1 pans, or forty (40) full-size hotel pans (GN 1/1), includes twenty (20) non-tilt support rails, and ten (10) stainless steel shelves.

**FACTORY INSTALLED OPTIONS**

Boiler Version

**Electrical Choices**

- 208-240V 3ph  380-415V 3ph  
 440-480V 3ph

**Door Swing**

- Right-hand Door Hinging, standard  
 Recessed Door, optional; increases oven width by 4" (102mm), slides out of the way for safety and frees up aisle space

Extended One-year Warranty

Installation Start-Up Check - AVAILABLE THROUGH AN ALTO-SHAAM AUTHORIZED SERVICE AGENCY


**Probe Choices**

- Removable, single-point, quick-connect core temperature probe, optional  
 Removable, single-point, quick-connect sous vide temperature probe, optional

**Security Devices for correctional facility use**

- Optional base package: includes tamper-proof screw package, excludes temperature probe  
 Anti entrapment device, optional  
 Control panel security cover, optional  
 Hasp door lock (padlock not included), optional  
 Removable, single-point, quick-connect core temperature probe, optional  
 Seismic feet package, optional





**DIMENSIONS: H x W x D**

**EXTERIOR:**

79-1/4" x 43-3/4" x 47" (2012mm x 1111mm x 1192mm)

**EXTERIOR WITH RECESSED DOOR:**

79-1/4" x 47-3/4" x 47" (2012mm x 1213mm x 1192mm)

**INTERIOR:**

60-7/16" x 24-1/4" x 32-3/4" (1535mm x 616mm x 832mm)

<b>WATER REQUIREMENTS</b>	
<b>TWO (2) COLD WATER INLETS - DRINKING QUALITY</b>	
<b>ONE (1) TREATED WATER INLET:</b>	3/4" NPT* * Can manifold off of one 3/4" line.
<b>ONE (1) UNTREATED WATER INLET:</b>	3/4" NPT*
<b>LINE PRESSURE:</b>	30 to 90 psi 2.1 to 6.3 bar
<b>WATER DRAIN:</b> 1-1/2" (40mm) CONNECTION WITH A 2" MINIMUM AIR GAP INSTALLED AS CLOSE TO THE OVEN AS POSSIBLE. MATERIALS MUST WITHSTAND TEMPERATURES UP TO 200°F (93°C).	
<b>CLEARANCE REQUIREMENTS</b>	
<b>LEFT:</b> 0" (0mm)	18" (457mm) FOR SERVICE ACCESS
<b>RIGHT:</b> 0" (0mm) NON-COMBUSTIBLE SURFACES	2" (51mm) COMBUSTIBLE SURFACES
<b>TOP:</b> 20" (508mm) FOR AIR MOVEMENT	
<b>BACK:</b> 4" (102mm)	<b>BOTTOM:</b> 5-1/8" (130mm) FOR LEGS, AIR INTAKE
<b>INSTALLATION REQUIREMENTS</b>	
• Oven must be installed level. • Hood installation is required.	
• Water supply shut-off valve and back-flow preventer when required by local code.	

<b>WATER QUALITY STANDARDS</b>	
It is the sole responsibility of the owner/operator/purchaser of this equipment to verify that the incoming water supply is comprehensively tested and if required, a means of "water treatment" provided that would meet compliance requirements with the published water quality standards published below. Non-compliance with these minimum standards will potentially damage this equipment and/or components and VOID the original equipment manufacturer's warranty. Alto-Shaam recommends using OptiPure® [www.optipurewater.com] products to properly treat your water.	
<b>Contaminant</b>	<b>Inlet Water Requirements</b>
Free Chlorine	Less than 0.1 ppm (mg/L)
Hardness	30-70 ppm
Chloride	Less than 30 ppm (mg/L)
pH	7.0 to 8.5
Silica	Less than 12 ppm (mg/L)
Total Dissolved Solids (tds)	50-125 ppm

**ELECTRICAL (NO CORD, NO PLUG, DEDICATED CIRCUIT REQUIRED) DO NOT CONNECT TO A G.F.I. OUTLET**

MODEL	VOLTAGE	PH	HZ	AMPS	kW	BREAKER	AWG	CONNECTION
CTC20-20E	208 – 240	3	50/60	137.6 – 158.8	49.6 – 66	150-175	4/0	L1, L2, L3, G
	380 – 415	3	50	84.2 – 91.7	56.4 – 66	100	1 – 1/0	L1, L2, L3, N, G
	440 – 480	3*	60	72.7 – 79.4	56.5 – 66	80	2 – 1	L1, L2, L3, G

\*ELECTRICAL SERVICE CHARGE APPLIES

WEIGHT		SHIP DIMENSIONS		PAN CAPACITY		PRODUCT MAXIMUM: 480 lb (218 kg)	
NET	1100 lbs est 499 kg	(L x W x H)	53" x 53" x 87"	FULL-SIZE:	20" x 12" x 2-1/2"	Forty (40)	VOLUME MAXIMUM: 300 quarts (380 liters)
SHIP	1150 lbs* 522 kg*	(1346 x 1346 x 2210mm)*		*ON WIRE SHELVES ONLY	GN 1/1: 530 x 325 x 65mm	Forty (40)	
*DOMESTIC GROUND SHIPPING INFORMATION. CONTACT FACTORY FOR EXPORT WEIGHT AND DIMENSIONS.					GN 2/1: 650 x 530 x 65mm	Twenty (20)	*ADDITIONAL WIRE SHELVES REQUIRED FOR MAXIMUM CAPACITY
				*FULL-SIZE SHEET:	18" x 26" x 1"	Twenty (20)	