

PRODUCT:

QUANTITY:

Stationary Models SST-2 SST-3 SST-4 SST-5
Portable Models PSST-2 PSST-3 PSST-4 PSST-5
ITEM:

Designed Smart

APW Hot Well Sealed Element Steam Tables individual sealed wells are fully covered and constructed of type 304 stainless steel.

- Individual infinite switch heat controls; thermostatic also available
- Indicator light remains on while control is in ON position
- Standard with 750 watt elements; 1200 and 1600 watt elements are available
- Deep drawn type 304 stainless steel well
- Fully welded drain
- Copper manifold with gate valve is standard
- ½" thick poly cutting board mounted on stainless steel shelf supported by stainless steel brackets
- Available with either, stainless steel legs and under shelf or coated steel legs and under shelf
- Cord and plug included with standard units



Model: SST5

APW Wyott Design Features

Heavy gauge stainless steel construction for the body. Individual controls allow for wet or dry application.

Features include:

- Poly cutting board
- Stainless steel dish shelf
- High-output tubular heating elements.
- Stationary and portable units available.
- UL and UL Sanitation approved
- Full range of options and accessories.
- All wells complete with drains running to a common all-copper manifold complete with ball valve

Reliability Backed by APW Wyott's Warranty

All APW Wyott cooking equipment is backed by a 1-year limited warranty and a 1-year on-site labor warrant. *

Certified by the following agencies:



Options and Accessories

Cutting Boards

- NSF approved Plastic Cutting Boards – 7 1/2" X 12"
- Hardwood – 8" X 1-1/4"
- Richlite Heat-Resistant – 8" X 12"

- Serving Shelves with Glass Protector
- Plate Shelves
- Tubular Tray Slide – 3-Bar
- Buffet Shelves
- Spillage Pans
- Adjustable Overall Shelf System
- Pot Hooks
- Deluxe Serving Shelves
- Solid Tray Slide
- Rolltop Covers
- Adapter Bars for Food Pans – 10" X 12"
- Adapter Tops for Round Inserts – 4-, 7-, and 11-Quart
- Auto Fill

Stationary Models SST-2 SST-3 SST-4 SST-5
 Portable Models PSST-2 PSST-3 PSST-4 PSST-5
 ITEM:

PRODUCT:

QUANTITY:

PRODUCT SPECIFICATIONS

Construction:

Individual sealed wells are fully covered and constructed of type 304 stainless steel.

Freight Class: 85

FOB: Standex Dock

Stationary

Non-Markina feet adjust unit height from 34 1/2" to 35 1/2".

Model #	# of top openings	Length	Weight	Electrical data
SST-120-2	2	31 3/8"	101 lbs	1500W, 120V, 12.5A
SST-208-2	2	31 3/8"	101 lbs	1500W, 180V, 7.21A
SST-240-2	2	31 3/8"	101 lbs	1500W, 240V, 6.25A
SST-120-3	3	45 3/4"	129 lbs	2250W, 120V, 18.8A
SST-208-3	3	45 3/4"	129 lbs	2250W, 180V, 10.82A
SST-240-3	3	45 3/4"	129 lbs	2250W, 240V, 11.9A
SST-120-4	4	60 1/8"	162 lbs	3000W, 120V, 25.0A
SST-208-4	4	60 1/8"	162 lbs	3000W, 208V, 14.42A
SST-240-4	4	60 1/8"	162 lbs	3000W, 240V, 15.8A
SST-120-5	5	74 1/2"	199 lbs	3750W, 120V, 31.3A
SST-208-5	5	74 1/2"	199 lbs	3750W, 208V, 18.3A
SST-240-5	5	74 1/2"	199 lbs	3750W, 240V, 19.8A

Portable

Push handle and 4" – diameter casters, two with brake included

AutoFill® Automatic Water System

For AutoFill add "A" to the front of the Model number. Example: ASST-120-2

Model #	# of top openings	Length	Weight	Electrical data
PSST-120-2	2	31 3/8"	101 lbs	1500W, 120V, 12.5A
PSST-208-2	2	31 3/8"	101 lbs	1500W, 208V, 7.21A
PSST-240-2	2	31 3/8"	101 lbs	1500W, 240V, 6.25A
PSST-120-3	3	45 3/4"	129 lbs	2250W, 120V, 18.8A
PSST-208-3	3	45 3/4"	129 lbs	2250W, 208V, 10.82A
PSST-240-3	3	45 3/4"	129 lbs	2250W, 240V, 11.9A
PSST-120-4	4	60 1/8"	162 lbs	3000W, 120V, 25.0A
PSST-208-4	4	60 1/8"	162 lbs	3000W, 208V, 14.42A
PSST-240-4	4	60 1/8"	162 lbs	3000W, 240V, 15.8A
PSST-120-5	5	74 1/2"	199 lbs	3750W, 120V, 31.3A
PSST-208-5	5	74 1/2"	199 lbs	3750W, 208V, 18.3A
PSST-240-5	5	74 1/2"	199 lbs	3750W, 240V, 19.8A

Receptacle configurations required for Sealed Well Food Tables.

15 AMP 125V	15 AMP 250V	20 AMP 250V	30 AMP 125V	30 AMP 250V	50 AMP 125V
model #	model #	model #	model #	model #	model #
S(P)HT2-120	S(P)HT2-240	S(P)HT4-240	S(P)HT3-120	S(P)HT5-240	S(P)HT4-120
furnished with NEMA 5-15 plug	furnished with NEMA 6-15 plug	furnished with NEMA 6-20 plug	furnished with NEMA 5-30 plug	furnished with NEMA 6-30 plug	furnished with NEMA 5-50 plug

*APW Wyott reserves the right to modify specifications or discontinue models without incurring obligation.