

Stationary Models ST-2 ST-3 ST-4 ST-5
 Portable Models PST-2 PST-3 PST-4 PST-5
 ITEM:

PRODUCT:

QUANTITY:

Designed Smart

APW Hot Well Sealed Exposed Element Steam Tables constructed of stainless steel with die stamped top.

- Individual infinite switch heat controls; thermostatic also available
- Indicator light remains on while control is in ON position
- Standard with 500 watt elements; 750 watt elements also available
- Stainless steel liner is standard
- Each compartment insulated with 1" thick fiberglass
- ½" thick poly cutting board mounted on stainless steel shelf supported by stainless steel brackets
- Available with either, stainless steel legs and under shelf or coated steel legs and under shelf
- Cord and plug included with standard units



Model: ST5

APW Wyott Design Features

Heavy gauge stainless steel construction for the body.

Features include:

- Poly cutting board
- Stainless steel dish shelf
- High-output tubular heating elements.
- Stationary and portable units available.
- UL and UL Sanitation approved
- Full range of options and accessories.
- Individual controls for peak performance
- Recessed controls for improved protection and safety

Reliability Backed by APW Wyott's Warranty

All APW Wyott cooking equipment is backed by a 1-year limited warranty and a 1-year on-site labor warrant. *

Certified by the following agencies:



Options and Accessories

Cutting Boards

- NSF approved Plastic Cutting Boards – 7 1/2" X 12"
- Hardwood – 8" X 1-1/4"
- Richlite Heat-Resistant – 8" X 12"

- Serving Shelves with Glass Protector
- Plate Shelves
- Tubular Tray Slide – 3-Bar
- Buffet Shelves
- Spillage Pans
- Adjustable Overall Shelf System
- Pot Hooks
- Deluxe Serving Shelves
- Solid Tray Slide
- Rolltop Covers
- Adapter Bars for Food Pans – 10" X 12"
- Adapter Tops for Round Inserts – 4-, 7-, and 11-Quart
- Auto Fill

Stationary Models ST-2 ST-3 ST-4 ST-5
 Portable Models PST-2 PST-3 PST-4 PST-5
 ITEM:

PRODUCT:

QUANTITY:

PRODUCT SPECIFICATIONS

Construction:

All stainless steel wrapper. Individual controls for peak performance.

Freight Class: 85

FOB: Standex Dock

Stationary

Non-Marking feet adjust unit height from 34 1/2" to 35 1/2".

Model #	# of top openings	Length	Weight	Electrical data
ST-120-2	2	31 3/8"	97	1000W,120V,8.33Amps
ST-208-2	2	31 3/8"	97	1500W,208V,7.21Amps
ST-240-2	2	31 3/8"	97	1500W,240V,6.25Amps
ST-120-3	3	45 3/4"	125	1500W,120V,12.5Amps
ST-208-3	3	45 3/4"	125	2250W,208V,10.82Amps
ST-240-3	3	45 3/4"	125	2250W,240V,9.38Amps
ST-120-4	4	60 1/8"	158	2000W,120V,16.67Amps
ST-208-4	4	60 1/8"	158	3000W,208V,14.42Amps
ST-240-4	4	60 1/8"	158	3000W,240V,12.5Amps
ST-120-5	5	74 1/2"	193	2500W,120V,20.83Amps
ST-208-5	5	74 1/2"	193	3750W,208V,18.03Amps
ST-240-5	5	74 1/2"	193	3750W,240V,15.63Amps

Portable

Push handle and 4" – diameter casters, two with brake included

Model #	# of top openings	Length	Weight	Electrical data
PST-120-2	2	31 3/8"	97	1000W,120V,8.33Amps
PST-208-2	2	31 3/8"	97	1500W,208V,7.21Amps
PST-240-2	2	31 3/8"	97	1500W,240V,6.25Amps
PST-120-3	3	45 3/4"	125	1500W,120V,12.5Amps
PST-208-3	3	45 3/4"	125	2250W,208V,10.82Amps
PST-240-3	3	45 3/4"	125	2250W,240V,9.38Amps
PST-120-4	4	60 1/8"	158	2000W,120V,16.67Amps
PST-208-4	4	60 1/8"	158	3000W,208V,14.42Amps
PST-240-4	4	60 1/8"	158	3000W,240V,12.5Amps
PST-120-5	5	74 1/2"	193	2500W,120V,20.83Amps
PST-208-5	5	74 1/2"	193	3750W,208V,18.03Amps
PST-240-5	5	74 1/2"	193	3750W,240V,15.63Amps

15 AMP 125V	15 AMP 250V	20 AMP 250V	30 AMP 125V	30 AMP 250V	50 AMP 125V
model #	model #	model #	model #	model #	model #
S(P)HT2-120	S(P)HT2-240	S(P)HT4-240	S(P)HT3-120	S(P)HT5-240	S(P)HT4-120
furnished with NEMA 5-15 plug	S(P)HT3-240 furnished with NEMA 6-15 plug	furnished with NEMA 6-20 plug	furnished with NEMA 5-30 plug	furnished with NEMA 6-30 plug	furnished with NEMA 5-50 plug

*APW Wyott reserves the right to modify specifications or discontinue models without incurring obligation.