

Models | WS-2 | WS-3 | WS-4 | WS-5 | WS-6

PRODUCT: QUANTITY: ITEM:

Designed Smart

Dependable Heat for Your Warming Needs!

- · APW Wyott Warming Shelves are designed to hold all potentially hazardous foods at required NSF temperatures.
- · Unique rope heat system provides uniform heat to your
- Designed to provide a rapid heat start-up to bring temperatures up to 212 degrees.

Excellent for all Serving Occasions!

- Ideal for server-to-customer pass-through areas. cafeteria, and buffet lines.
- · Provided in 5 different lengths for your specific serving requirements.
- Built with 1/2" rubber feet to prevent the unit from sliding while on the serving line.

Easy to Clean!

· Stainless steel surfaces wash off easier and withstand repeated abuse.

APW Wyott Design Features

- Stainless steel construction resists corrosion and wear and tear from incremental handling in serving areas
- Infinite temperature control knob on operator side.
- · Six foot cord and plug.
- ½" natural rubber feet.



Model WS-3 Warming Shelf



Model WS-5 Warming Shelf

Reliability backed by APW Wyott's Warranty

All APW Wyott Warming Shelves are backed by a 1-year limited warranty and a 1-year on-site labor warrant.

· Certified by the following agencies









See reverse side for product specifications.




^{*}Warranty does not include rock grates, cooking grates, burners shields or fireboxes.



Models | WS-2 | WS-3 | WS-4 | WS-5 | WS-6

PRODUCT: QUANTITY: ITEM:



Α			
WS-2	24"	WS-5	60"
WS-3	36"	WS-6	72"
WS-4	48"		



PRODUCT SPECIFICATION

Construction:

Stainless steel construction, 1/2" rubber feet.

Electrical Information:

120V units come with 6' cord and NEMA5-15P plug. 220V unites come with 6' cord and EURO plug (CE unit). 208/240V units come with 6' cord and NEMA 6-15P plug.

Electrical Specifications:

WS-2: 120V,200W, 60 Hz, 1.7Amps 208V, 200W, 1.0 Amps 220V, 200W, 0.9 Amps 240V, 200W, 0.8 Amps

WS-3: 120V, 300W, 60Hz, 2.5 Amps 208V, 300W, 1.4 Amps 220V, 300W, 1.3 Amps 240V, 300W, 1.2 Amps

WS-4: 120V, 400W, 60 Hz, 3.3 Amps 208V, 400W, 1.9 Amps 220V, 400W, 1.8 Amps

220V, 400W, 1.8 Amps 240V, 400W, 1.7 Amps

WS-5: 120V, 500W, 60 Hz, 4.2 Amps

208V, 500W. 2.4 Amps 220V, 500W, 2.2 Amps 240V, 500W, 2.1 Amps

WS-6: 120V, 600W, 60 Hz, 5.0 Amps

208V, 600W, 2.9 Amps 220V, 600W, 2.7 Amps 240V, 600W, 2.5 Amps

Overall Dimensions:

WS-2: 2 3/8"H x 18'W x 24"L

(60 cm x 45.7 cm x 61.0 cm)

WS-3: 2 3/8"H x 18'W x 24"L

(60 cm x 45.7 cm x 61.0 cm

WS-4: 2 3/8"H x 18'W x 24"L (60 cm x 45.7 cm x 61.0 cm

2 3/8"H x 18'W x 24"L

(60 cm x 45.7 cm x 61.0 cm

WS-6: 2 3/8"H x 18'W x 24"L

(60 cm x 45.7 cm x 61.0 cm

Shipping:

WS-5:

WS-2: 27 lbs (12.3kg) WS-5: 56 lbs (25.5kg) WS-3: 38 lbs (17.2kg) WS-6: 70 lbs (31.8kg)

WS-4: 49 lbs (22.7kg)

Freight Class: 85 FOB: Cheyenne, WY 82007

^{*}APW Wyott reserves the right to modify specifications or discontinue models without incurring obligation.

