



COMMERCIAL REFRIGERATION

223 W. Rosecrans Ave., Gardena, CA 90248

Toll Free 1.866.677.8500 T. 310.808.0102, F. 310.808.0242

www.blueairinc.com | info@blueairinc.com

PROJECT :	
MODEL # :	
ITEM # :	QTY :
AVAILABLE W/H :	
APPROVAL :	

Glass Door Freezer

K-Series

MODEL: BKGF49

STANDARD FEATURES

BOTTOM MOUNT COMPRESSOR

The bottom mount compressor structure is placed in the coolest possible area, provides quick and easy maintenance

PAINTED STEEL EXTERIOR AND PAINTED ALUMINUM INTERIOR

DIGITAL TOTAL MONITORING SYSTEM

Offers easy temperature adjustment and a simple to control defrost cycle

SELF-CLOSING DOORS

TRIPLE PANE GLASS DOORS

4 CASTERS WITH 2 LEVELING LEGS



Model	Doors	Capacity (Cu.Ft)	Shelves	Cabinet Dimensions (inch / mm)			HP	Voltage	Amps	NEMA Config.	Cord Length (ft / m)	Net Weight (lbs / kg)
				W	D	H						
BKGF49	2	49	8 ea	54 3/8" 1382	31 1/2" 800	81 1/4" 2065	3/4	115V/60Hz	12	NEMA5-15	9.8 2.9	456 207



WARRANTY
2 Years Parts and Labor
5 Years on Compressor in USA

APPROVALS:

AVAILABLE AT:

MODEL: BKGF49

PRODUCT SPECIFICATION

Product Description	Freezer
Capacity(Cu.ft.)	49
Exterior Dimensions (WxDxH)	54 3/8" x 31 1/2" x 81 1/4" 1382 x 800 x 2065 mm
Net Weight (lbs / kg)	456 / 207
Foot	4 Casters
Door Type	2 Glass Door (Swing)
Door Stopper	NONE
Shelves	8 ea
Input	AC 115V/60Hz
Amps	12 A
Compressor(Hp)	3/4 HP
Refrigerant	R-404a
Range of Temperature	below 0°F
Easy maintenance	Sliding Condensing Unit

* BLUE AIR has the right to change specifications without further notice.

STANDARD FEATURES

- Refrigeration system is optimized to function below 0°F
- Air guard on shelf ensures proper air flow and cooling
- Evaporator fan stops when door open
- Interior LED light and LED AD panel
- 2" Diameter swivel casters and 2 leveling legs
- High density cell polyurethane insulation(CFC Free)
- 4 Shelves per each door section
- 1" Adjustable shelving heights
- Each door is equipped with individual lock
- Durable door gasket with easy replacement
- Triple pane glass doors
- Fabric condensation kit

PLAN VIEW

