

www.blueairinc.com | info@blueairinc.com

| PROJECT: | |
|----------------|------|
| MODEL #: | |
| ITEM #: | QTY: |
| AVAILABLE W/H: | |
| APPROVAL: | |

Glass Door Merchandiser

K-Series

MODEL: BKGM14

STANDARD FEATURES

BOTTOM MOUNT COMPRESSOR

The bottom mount compressor structure is placed in the coolest possible area, provides quick and easy maintenance

PAINTED STEEL EXTERIOR AND PAINTED ALUMINUM INTERIOR

DIGITAL TOTAL MONITORING SYSTEM

Offers easy temperature adjustment and a simple to control defrost cycle

SELF-CLOSING DOOR

DOUBLE PANE GLASS DOOR

4 CASTERS WITH 2 LEVELING LEGS



| | | Capacity | | Cabinet Dimensions (inches) | | | | | _ | NEMA | Cord Length | Net Weight |
|--------|-------|-----------|---------|-----------------------------|----|---------|-----|-----------|------|----------|----------------|---------------|
| Model | Doors | (Cu. Ft.) | Shelves | L | D | Н | HP | Voltage | Amps | Config. | (ft) | (lbs) |
| BKGM14 | 1 | 14 | 4 ea | 24 1/4" | 24 | 76 1/4" | 1/5 | 115V/60Hz | 3.2 | NEMA5-15 | 9.8 | 208 |



Conforms to NSF/ANSI 7(ETL)

WARRANTY

2 Years Parts and Labor

5 Years on Compressor in USA

| APPROVALS: | | |
|------------|--|--|
| | | |
| | | |

AVAILABLE AT:

MODEL: BKGM14

PRODUCT SPECIFICATION

| I | Product Description | Refrigerator |
|---|----------------------------|--------------------------------|
| ī | Capacity(Cu.ft.) | 14 |
| I | Exterior Dimensions(WxDxH) | 24 1/4" x 24" x 76 1/4" |
| ī | Net Weight(lbs) | 208 |
| I | Foot | 4 Casters with 2 leveling legs |
| Ī | Door Type | 1 Glass Door (Swing) |
| I | Door Stopper | NONE |
| ī | Shelves | 4 ea |
| I | Input | AC 115V/60Hz |
| ī | Amps | 3.2 A |
| I | Compressor(Hp) | 1/5 HP |
| Ī | Refrigerant | R-134a |
| I | Range of Temperature | 32-40°F |
| Ī | Easy maintenance | Sliding Condensing Unit |
| | | |

^{*} BLUE AIR has the right to change specifications without further notice.

STANDARD FEATURES

- Refrigeration system is optimized to function between 32-40°F
- Air guard on shelf ensures proper air flow and cooling
- Evaporator fan stops when door open
- Interior LED light and LED AD panel
- 2" Diameter swivel casters and 2 leveling legs
- High density cell polyurethane insulation(CFC Free)
- 4 Shelves per each door section
- 1" Adjustable shelving heights
- Each door is equipped with individual lock
- Durable door gasket with easy replacement
- Double pane glass door
- Fabric condensation kit

PLAN VIEW Unit: inch [mm]



