



COMMERCIAL REFRIGERATION

223 W. Rosecrans Ave., Gardena, CA 90248

Toll Free 1.866.677.8500 T. 310.808.0102, F. 310.808.0242

www.blueairinc.com | info@blueairinc.com

PROJECT :	
MODEL # :	
ITEM # :	QTY :
AVAILABLE W/H :	
APPROVAL :	

Glass Door Mechandiser

K-Series

MODEL: BKGM48SL

STANDARD FEATURES

BOTTOM MOUNT COMPRESSOR

The bottom mount compressor structure is placed in the coolest possible area, provides quick and easy maintenance

PAINTED STEEL EXTERIOR AND PAINTED ALUMINUM INTERIOR

DIGITAL TOTAL MONITORING SYSTEM

Offers easy temperature adjustment and a simple to control defrost cycle

SLIDING SELF-CLOSING DOORS

DOUBLE PANE GLASS DOORS

4 CASTERS WITH 2 LEVELING LEGS



Model	Doors	Capacity (Cu. Ft.)	Shelves	Cabinet Dimensions (inches)			HP	Voltage	Amps	NEMA Config.	Cord Length (ft)	Net Weight (lbs)
				L	D	H						
BKGM48SL	2	48	8 ea	54 3/8"	30"	81 1/4"	1/4	115V/60Hz	4.3	NEMA5-15	9.8	395



Conforms to NSF/ANSI 7(ETL)

WARRANTY
 2 Years Parts and Labor
 5 Years on Compressor in USA

APPROVALS:

AVAILABLE AT:

VER0731

MODEL BKGGM48SL

PRODUCT SPECIFICATION

Product Description	Freezer
Capacity(Cu.ft.)	48
Exterior Dimensions(WxDxH)	54 3/8" x 30" x 81 1/4"
Net Weight(lbs)	395
Foot	4 Casters with 2 leveling legs
Door Type	2 Glass Door (Sliding)
Door Stopper	NONE
Shelves	8 ea
Input	AC 115V/60Hz
Amps	4.3 A
Compressor(Hp)	1/4 HP
Refrigerant	R-134a
Range of Temperature	32~40°F
Easy maintenance	Sliding Condensing Unit

STANDARD FEATURES

- Refrigeration system is optimized to function between 32-40°F
- Air guard on shelf ensures proper air flow and cooling
- Evaporator fan stops when door open
- Interior LED light and LED AD panel
- 2" Diameter swivel casters and 2 leveling legs
- High density cell polyurethane insulation(CFC Free)
- 4 Shelves per each door section
- 1" Adjustable shelving heights
- Durable door gasket with easy replacement
- Double pane glass doors
- Fabric condensation kit
- Sliding Self closing Doors

* BLUE AIR has the right to change specifications without further notice.

PLAN VIEW

