

PROJECT:	
MODEL #:	
ITEM #:	QTY:
AVAILABLE W/H:	
APPROVAL:	

## Glass Door Merchandiser

K-Series

MODEL: BKGM49

## STANDARD FEATURES

#### **BOTTOM MOUNT COMPRESSOR**

The bottom mount compressor structure is placed in the coolest possible area, provides quick and easy maintenance

# PAINTED STEEL EXTERIOR AND PAINTED ALUMINUM INTERIOR

## DIGITAL TOTAL MONITORING SYSTEM

Offers easy temperature adjustment and a simple to control defrost cycle

**SELF-CLOSING DOORS** 

**DOUBLE PANE GLASS DOORS** 

4 CASTERS WITH 2 LEVELING LEGS



	_	Capacity	<u>.</u>	Cabinet Dimensions (inches)				NEMA	Cord Length	Net Weight		
Model	Doors	(Cu. Ft.)	Shelves	L	D	Н	HP	Voltage	Amps	Config.	(ft)	(lbs)
BKGM49	2	49	8 ea	54 3/8"	31 1/2"	81 1/4"	1/4	115V/60Hz	4.3	NEMA5-15	9.8	408



Conforms to NSF/ANSI 7(ETL)

WARRANTY

2 Years Parts and Labor

5 Years on Compressor in USA

APPROVALS:		

AVAILABLE AT:

## MODEL: BKGM49

#### PRODUCT SPECIFICATION

I	Product Description	Refrigerator
ī	Capacity(Cu.ft.)	49
I	Exterior Dimensions(WxDxH)	54 3/8" x 31 1/2" x 81 1/4"
ī	Net Weight(lbs)	408
I	Foot	4 Casters with 2 leveling legs
ī	Door Type	2 Glass Door (Swing)
I	Door Stopper	NONE
ī	Shelves	8 ea
I	Input	AC 115V/60Hz
ī	Amps	4.3 A
I	Compressor(Hp)	1/4 HP
Ī	Refrigerant	R-404a
I	Range of Temperature	32~40°F
Ī	Easy maintenance	Sliding Condensing Unit

<sup>\*</sup> BLUE AIR has the right to change specifications without further notice.

#### STANDARD FEATURES

- Refrigeration system is optimized to function between 32-40°F
- Air guard on shelf ensures proper air flow and cooling
- Evaporator fan stops when door open
- Interior LED light and LED AD panel
- 2" Diameter swivel casters and 2 leveling legs
- High density cell polyurethane insulation(CFC Free)
- 4 Shelves per each door section
- 1" Adjustable shelving heights
- Each door is equipped with individual lock
- Durable door gasket with easy replacement
- Double pane glass doors
- Fabric condensation kit

### **PLAN VIEW**



