

PROJECT:	
MODEL #:	
ITEM #:	QTY:
AVAILABLE W/H:	
APPROVAL:	

Bottom Mount Glass Door Reach in

D-Series

MODEL: BSR49G

STANDARD FEATURES

BOTTOM MOUNT COMPRESSOR

The bottom mount compressor structure is placed in the coolest possible area, provides quick and easy maintenance

OVERSIZED REFRIGERATION SYSTEM

STAINLESS STEEL INTERIOR AND EXTERIOR

The excellent quality of stainless steel minimizes dents, scratches and rust

DIGITAL TOTAL MONITORING SYSTEM

Offers an automatic door alarm system, easy temperature adjustment and a simple to control defrost cycle

SELF-CLOSING DOOR

DOUBLE PANE GLASS DOOR



	_	Capacity		Cabin	oinet Dimensions (inches)					NEMA	Cord Length	Net Weight
Model	Doors	(Cu. Ft.)	Shelves	L	D	Н	HP	Voltage	Amps	Config.	(ft)	(lbs)
BSR49G	2	49	8 ea	54"	31	82 3/8"	3/4	115V/60Hz	11.5	NEMA5-15	9.8	455



Conforms to NSF/ANSI 7(ETL)

WARRANTY

2 Years Parts and Labor

5 Years on Compressor in USA

APPROVALS:

AVAILABLE AT:

MODEL: BSR49G

PRODUCT SPECIFICATION

Ī	Product Description	Refrigerator
Ī	Capacity(Cu.ft.)	49
Ī	Exterior Dimensions(WxDxH)	54" x 31" x 82 3/8" WITHOUT HANDLE
Ī	Net Weight(lbs)	455
Ī	Foot	4 Casters
Ī	Door Type	2 Glass Doors (Swing)
I	Door Stopper	NONE
ī	Shelves	8 ea
I	Input	AC 115V/60Hz
ī	Amps	11.5 A
I	Compressor(Hp)	3/4 HP
ī	Refrigerant	R-134a
I	Range of Temperature	32 ~ 40°F
ī	Easy maintenance	Sliding Condensing Unit

^{*} BLUE AIR has the right to change specifications without further notice.

STANDARD FEATURES

- Refrigeration system is optimized to function between 32~40°F
- Air guard on rear wall ensures proper air flow and cooling
- Evaporator fan stops when door open
- Interior fluorescent light
- 4" Diameter swivel casters with brakes(front)
- High density cell polyurethane insulation(CFC Free)
- · Accommodates full size bun sheet pans
- 4 Shelves per each door section
- 1" Adjustable shelving heights
- Door open warning alarm
- Each door is equipped with individual lock
- Durable door gasket with easy replacement
- Double pane glass doors
- Fabric condensation kit

PLAN VIEW



