

STANDARD FEATURES

- ◆ 7½" high
- ◆ 1/5 hp direct driven motor(s)
- ◆ Factory installed "intelliswitch" digital programmable controller - *see features below*
- ◆ Aluminum air directional vanes
- ◆ Clear anodized aluminum exterior cabinet
- ◆ Wall mounting plate and ¼" threaded inserts for top mounting

- ◆ Aluminum cross-flow blower wheels
- ◆ UL Listed - Indoor Use (United States, Canada)
- ◆ Five year parts warranty
- ◆ Crafted with Pride in the USA

OPTIONAL FEATURES

- ◆ Bronze anodized aluminum finish
- ◆ Stainless steel finish

MODEL	Nozzle Width (in)	Max. Velocity (fpm)	Avg. Outlet Velocity (fpm)	Air Volume (scfm)	Motor(s) @ hp	Power Rating (kW)	Outlet Velocity Uniformity (%)	Net Wgt (lbs)	Ship Wgt (lbs)
ZPR1030A	28.00	3000	1777	691	1 @ 1/5	.18	89	33	42
ZPR1036A	35.25	3000	2118	1036	1 @ 1/5	.32	92	38	45
ZPR1042A	41.25	3000	2115	1212	1 @ 1/5	.32	93	43	50
ZPR1048A	47.25	3000	2104	1381	1 @ 1/5	.32	94	48	56
ZPR1060A	59.00	3000	2052	1682	1 @ 1/5	.32	95	57	65
ZPR1072A	72.50	3000	2118	2072	1 @ 1/5	.32	95	64	73
ZPR2084A	84.25	3000	2115	2424	2 @ 1/5	.64	93	86	95
ZPR2096A	96.25	3000	2104	2762	2 @ 1/5	.64	94	96	106
ZPR2120A	119.75	3000	2046	3364	2 @ 1/5	.64	95	114	130

MOTOR VOLTAGES/AMP DRAWS					
Volts	120	208	240	110*	220*
Phase	1	1	1	1	1
Hertz	60	60	60	50	50
Amps per Motor	3.4	1.7	1.7	2.8	1.4

* Operation at 50 Hz will generate approximately a 17% reduction in performance.

VELOCITY PROJECTION Model ZPR1036A			
Distance from Nozzle (ft)	2	3	4
Core Velocity (fpm)	1824	1509	1292

Sound level measured 10' (3m) from the unit in free field:
1 Motor **54 dBA**
2 Motors **57 dBA**



Intelliswitch Features

- ◆ Time Delay
- ◆ 10 Speed Fan Slection
- ◆ On/Off/Auto Operation
- ◆ Start/Stop Times
- ◆ Low Voltage Control Circuit
- ◆ Time Clock
- ◆ LED Display
- ◆ Lockable Display

Berner reserves the right to alter specifications without prior notice.