

# BEVERAGE-AIR

3779 Champion Blvd., Winston-Salem, NC 27105 1-888-845-9800 Fax# 1-336-245-6453 http://www.Beverage-Air.com

## CUSTOMER'S CHOICE FOR A HOT LOCATION Tested & Certified to Ambient Class of 100°F

# Item No. \_\_\_\_\_ Quantity \_\_\_\_\_

# **BEER EQUIPMENT** HINGED GLASS DOOR **BACK BAR REFRIGERATOR 23" BASE BB PASS-THRU SERIES**

**MODELS:** BB48GY-1-B/S-PT BB48GY-1-B/S-27-PT

BB72GY-1-B/S-PT BB72GY-1-B/S-27-PT

# 3 Year Parts/Labor Warranty Additional 2 Year Compressor Warranty

### BB HINGED GLASS DOORS — PASS-THRU BACK BAR REFRIGERATORS

23" base Pass-Thru, self-contained refrigerators come in two widths of 48" and 72."

23" base shallow depth units are available in two heights:

34" height with standard galvanized steel top for under shelf application and 36" height when adapted with a 2" stainless steel top (specify -27). Depth is 23 1/2" from face of door to opposite side of cabinet. Handle projects 1/2."

### **CABINET CONSTRUCTION**

Standard, cabinet exterior construction includes black steel finish. Stainless steel exterior option available (-S models).

Galvanized sub top standard. 2" stainless steel top optional (specify -27). Hinged glass doors are self-closing and include a stay-open feature and lock.

Standard interior construction utilizes galvanized steel walls and ceiling. Reinforced floor made from heavy-duty stainless steel to provide long lasting service.

Field-reversible doors with 90° stay-open feature standard.

Two (2) epoxy-coated shelves per section standard.

Interior, fluorescent lighting standard. Optional LED lighting.

Environmentally friendly foamed-in-place CFC and HCFC-free polyurethane insulation enhances the structural strength of the cabinet and helps increase energy efficiency.

### REFRIGERATION

Refrigeration is fully accessible behind grille to right side of cabinet and is 100% front breathing.

Evaporator located above condensing unit permits full use of interior spaces.

Refrigeration system uses R134a refrigerant, which is CFC and HCFC-free for compliance with environmental safety concerns.

Remote refrigeration models available.

### **ELECTRICAL**

Units are pre- wired at factory and ready for connection to a 115/60/1 phase, 15 amp dedicated outlet. 8' long cord and plug set included.





BB48GY-1-B-PT

### **AVAILABLE OPTIONS**

- LED lighting
- Wire shelf dividers
- 3" or 6" casters; 6" legs
- WINE models available (40°-60°F models)
- Open-Food Rated models available











\*Note: Not all markings may apply to all model variations.

Available From:

Model Specified	Store#
Location	Quantity




Back Bar Hinged Glass Door Refrigerator—Pass-Thru Models: BB48GY-1-B/S-PT, B48GY-1-B/S-27-PT, BB72GY-1-B/S-PT, BB72GY-1-B/S-27-PT

MODEL	BB48GY-1-B/S-PT	BB48GY-1-B/S-27-PT (2" S/S TOP)	BB72GY-1-B/S-PT	BB72GY-1-B/S-27-PT (2" S/S TOP)
EXTERNAL DIMENSIONAL DATA				
Length Overall (inches) Length Overall (mm)	48" 1219	48" 1219	72" 1829	72" 1829
Depth Overall (inches) Depth Overall (mm)	25" 635	25" 635	25" 635	25" 635
Height Overall— (inches) Height Overall—(mm)	34" 864	36" 914	34" 864	36" 914
Number of doors	2	2	3	3
INTERNAL DIMENSIONAL DATA				
NET Capacity (cubic ft.) NET Capacity (Liters)	12.1 343	12.1 343	19.4 549	19.4 549
Internal Length Overall (inches) Internal Length Overall (mm)	36" 914	36" 914	60" 1524	60" 1524
Internal Depth Overall (inches) Internal Depth Overall (mm)	18 1/2" 470	18 1/2" 470	18 1/2" 470	18 1/2" 470
Internal Height Overall (inches) Internal Height Overall (mm)	29 1/2" 749	29 1/2" 749	29 1/2" 749	29 1/2" 749
Number of Shelves	4	4	6	6
Number of Kegs (1/2 barrel)	2	2	3	3
ELECTRICAL DATA				
Full Load Amperes 115/60/1	5	5	5	5
REFRIGERATION DATA				
Horsepower	1/4	1/4	1/4	1/4
WEIGHT DATA				
Gross Weight (Crated lbs)	306	306	366	366
Gross Weight (Crated kg)	139	139	166	166

# 25" OVERALL DEPTH 29 1/2" INSIDE HT END

**PLAN VIEWS** 

### BB48GY/BB72GY



BB48GY-1-B-PT (-27 models add 2" to height)












\*Note: Not all markings may apply to all model variations.



FRONT BB72GY-1-B-PT
(-27 models add 2" to height)