



BEVERAGE-AIR

3779 Champion Blvd., Winston-Salem, NC 27105 1-888-845-9800 Fax# 1-336-245-6453 http://www.Beverage-Air.com

Commercial Refrigeration Equipment General Specification

3 Year Parts/Labor Warranty Additional 2 Year Compressor Warranty

BB GLASS DOOR — PASS-THRU BACK BAR REFRIGERATORS WITH SLIDING GLASS DOORS

Pass-Thru, shallow depth back bar, self-contained refrigerators come in two widths of 48" and 72." BB48GSY-1-B-PT includes 2 sliding glass doors per side. BB72GSY-1-B-PT includes 3 sliding glass doors per side. Two heights include 34" with standard galvanized steel top for under shelf application and 36" when adapted with a stainless steel top (-27 models). Depth is 23" from face of door to back of cabinet. Handle projects 1/2.

CABINET CONSTRUCTION

Standard, cabinet exterior construction includes black steel finish. Stainless steel models available. Galvanized sub top standard on BB48GSY-1-B and BB72GSY-1-B. 2" stainless steel top optional (specify -27).

Sliding glass doors are self-closing and includes a stay-open feature and lock.

Standard interior construction utilizes galvanized steel walls and ceiling. Reinforced floor made from heavy-duty stainless steel to provide long lasting service. Interior, fluorescent lighting is standard.

Environmentally friendly foamed-in-place CFC and HCFC-free polyurethane insulation enhances the structural strength of the cabinet and helps increase energy efficiency.

REFRIGERATION

Refrigeration is fully accessible behind grille to right side of cabinet. Evaporator located above condensing unit permits full use of interior spaces. Forced air is projected the length of cabinet across the ceiling. Refrigeration system uses R134a refrigerant, which is CFC and HCFCfree for compliance with environmental safety concerns. Remote refrigeration models include expansion valve installed.

Condensate elimination is automatic and non-electric.

Interior, fluorescent lighting standard. Optional LED lighting.

ELECTRICAL

Units are wired at factory and ready for connection to a 115/60/1 phase, 15 amp dedicated outlet. 8' long cord and plug set included.







*Note: Not all markings may apply to all model variations.

BEER EQUIPMENT SLIDING GLASS DOOR BACK BAR REFRIGERATOR 23" BASE BB PASS-THRU SERIES

MODELS: BB48GSY-1-B-PT BB48GSY-1-B-PT-27

BB72GSY-1-B-PT BB72GSY-1-B-PT-27



BB48GSY-1-B-PT



BB48GSY-1-S-27-PT (shown in s/s exterior with 2" s/s top)

AVAILABLE OPTIONS:

- LED lighting
- Wire shelf dividers
- 3" or 6" casters; 6" legs
- WINE models available (40°-60°F models)
- Open-Food Rated models available

Available From:

Store#

Location

Quantity




BEVERAGE-AIR


PLAN VIEWS

Back Bar Glass Door Refrigerator—Pass-Thru Sliding Glass Doors Models: BB48GSY-1-B-PT, BB72GSY-1-B-PT

| MODEL | BB48GSY-1-B-PT | BB48GSY-1-B-PT-27 (2" S/S TOP) | BB72GSY-1-B-PT | BB72GSY-1-B-PT-27 (2" S/S TOP) |
|--|----------------|-----------------------------------|----------------|-----------------------------------|
| EXTERNAL DIMENSIONAL DATA | | | | |
| Length Overall (inches) Length Overall (mm) | 48" 1219 | 48" 1219 | 72" 1829 | 72" 1829 |
| Depth Overall (inches) Depth Overall (mm) | 25" 635 | 25" 635 | 25" 635 | 25" 635 |
| Height Overall— (inches) Height Overall—(mm) | 34" 864 | 36" 914 | 34" 864 | 36" 914 |
| Number of doors | 4 | 4 | 6 | 6 |
| INTERNAL DIMENSIONAL DATA | | | | |
| NET Capacity (cubic ft.) NET Capacity (Liters) | 12.1 343 | 12.1 343 | 19.4 549 | 19.4 549 |
| Internal Length Overall (inches) Internal Length Overall (mm) | 36" 914 | 36" 914 | 60" 1524 | 60" 1524 |
| Internal Depth Overall (inches) Internal Depth Overall (mm) | 18 1/2" 470 | 18 1/2" 470 | 18 1/2" 470 | 18 1/2" 470 |
| Internal Height Overall (inches) Internal Height Overall (mm) | 29 1/2" 749 | 29 1/2" 749 | 29 1/2" 749 | 29 1/2" 749 |
| Number of Shelves | 4 | 4 | 6 | 6 |
| Number of Kegs (1/2 barrel) | 2 | 2 | 3 | 3 |
| ELECTRICAL DATA | | | | |
| Full Load Amperes 115/60/1 | 5 | 5 | 5 | 5 |
| REFRIGERATION DATA | | | | |
| Horsepower | 1/4 | 1/4 | 1/4 | 1/4 |
| WEIGHT DATA | | | | |
| Gross Weight (Crated lbs) | 306 | 306 | 366 | 366 |
| Gross Weight (Crated kg) | 139 | 139 | 166 | 166 |










*Note: Not all markings may apply to all model variations.

ELECTRICAL CONNECTION

Units are pre-wired at factory and include 8' long cord and plug set.







FRONT

BB48GSY-1-B-PT

FRONT BB72GSY-1-B-PT

BEVERAGE-AIR® CORPORATION

Specifications are subject to change without prior notice. 07/13