

3779 Champion Blvd., Winston-Salem, NC 27105 1-888-845-9800 Fax# 1-336-245-6453 http://www.Beverage-Air.com

# Commercial Refrigeration Equipment General Specification

# DD 23" BASE SERIES—DIRECT DRAW DISPENSERS

Shallow depth, direct draw dispensers come in two widths of 48" and 72." Depth is 23" from face of door to back of cabinet. Handle projects 1/2."

### **CABINET CONSTRUCTION**

Standard, cabinet exterior construction includes attractive, wear resistant vinyl on steel in black exterior finish. Top is made from heavy-duty stainless steel including drip tray(s) for easy cleaning.

Doors are self-closing and include key locks. Magnetic gaskets provide positive door sealing.

Standard interior construction utilizes galvanized steel walls and ceiling. Reinforced floor and door sills are made from heavyduty stainless steel to provide long lasting service.

Foamed-in-place CFC and HCFC-free polyurethane insulation enhances the structural strength of the cabinet and helps increase energy efficiency.

Three-inch (3") insulated towers are provided. Towers are adapted to have a continuous source of cold air channeled into it to keep beer at its coldest, best quality the moment it is dispensed.

### REFRIGERATION


Models feature forced air refrigeration to keep beer in kegs ice cold for dispensing. Refrigeration system uses R134a refrigerant, which is CFC and HCFC-free for compliance with environmental safety concerns.

# **ELECTRICAL**

Units wired at factory and ready for connection to a 115/60/1 phase, 15 amp dedicated outlet. 8' long cord and plug set included.

# **SPECIAL FEATURES**

- Key locks
- Stainless options available



# DRAFT BEER EQUIPMENT DIRECT DRAW DISPENSERS 23" BASE DD SERIES

MODELS: DD48/DD48Y DD72/DD72Y















\*Note: Not all markings may apply to all model variations

Available From:

Model Specified	Store#
Location	Quantity



# Direct Draw Dispensers, 23" Base Models: DD48, DD48Y, DD72, DD72Y

MODEL	DD48	DD48Y	DD72	DD72Y
EXTERNAL DIMENSIONAL DATA				
Length Overall (inches) Length Overall (mm)	48" 1219	48" 1219	72" 1829	72" 1829
Depth Overall (inches) Depth Overall (mm)	23 1/2" 597	23 1/2" 597	23 1/2" 597	23 1/2" 597
Height Overall— (inches) Height Overall—(mm)	36" 914	36" 914	36" 914	36" 914
Clear Door Width (inches)	16 7/16" x 29 1/4"			
Depth With Door Open 90°	42 3/4"	42 3/4"	42 3/4"	42 3/4"
Number of doors	2	2	3	3
INTERNAL DIMENSIONAL DATA				
NET Capacity (cubic ft.) NET Capacity (Liters)	12.1 343	12.1 343	19.4 549	19.4 549
Internal Length Overall (inches) Internal Length Overall (mm)	36" 914	36" 914	60" 1524	60" 1524
Internal Depth Overall (inches) Internal Depth Overall (mm)	18 1/2" 470	18 1/2" 470	18 1/2" 470	18 1/2" 470
Internal Height Overall (inches) Internal Height Overall (mm)	29 1/2" 749	29 1/2" 749	29 1/2" 749	29 1/2" 749
Number of Kegs (straight wall)	2	2	3	3
ELECTRICAL DATA				
Full Load Amperes 115/60/1	6	5	6	5
ENERGY CONSUMPTION (KWH)	4.06	3.19	4.36	3.67
REFRIGERATION DATA				
Horsepower	1/4	1/4	1/4	1/4
WEIGHT DATA				
Gross Weight (Crated lbs)	314	314	377	377
Gross Weight (Crated kg)	142	142	171	171

# TOD48 72" FRONT

**DD72** 

**FRONT** 

**PLAN VIEWS** 

48"












\*Note: Not all markings may apply to all model variations.

# **ELECTRICAL CONNECTION**

Units pre-wired at factory and include 8' long cord and plug set.



**COMMON END VIEW** 



# **BEVERAGE-AIR® CORPORATION**