



BEVERAGE-AIR

3779 Champion Blvd., Winston-Salem, NC 27105 1-888-845-9800 Fax# 1-336-245-6453 http://www.Beverage-Air.com

Commercial Refrigeration Equipment General Specification

3 Year Parts/Labor Warranty Additional 2 Year Compressor Warranty

CABINET CONSTRUCTION

- Exterior—Stainless steel exterior.
- Interior—Stainless steel interior.
- Insulation—2" foamed-in-place CFC and HCFC-free polyurethane insulation.
- Will accept food carts (one per section) up to 27" wide x 29" deep x 64" high (supplied by others).
- Attachable door ramp of reinforced stainless steel includes a one-inch rise to the reinforced stainless steel cabinet floor.
- Stainless steel cart guides are included in the interior.

DIGITAL THERMOMETER

 Exterior digital thermometer provides a digital display of cabinet temperatures.

REFRIGERATION SYSTEM

- Top mount, environmentally friendly refrigeration system maintains product temperatures at 0°F.
- Factory engineered, self-contained refrigeration system uses environmentally friendly (CFC and HCFC-free) R404A refrigerant.

DOORS

- Solid door configuration.
- Anti-microbial door handles and door locks are standard.
- Field reversible doors and cam lift hinges standard. Positive seal self-closing door(s) with 120° stay open feature.
- Snap-in door gaskets of one piece construction, removable without tools for ease of cleaning.
- Wiper gasket at bottom of door seals door to ramp.

MODEL FEATURES

- Incandescent interior lighting.
- UL-EPH and CUL for open food product.

TOP MOUNTED ROLL-IN FREEZERS PFI SERIES SOLID DOORS MODELS: PFI1-1AS PFI2-5AS



PFI1-1AS



PFI2-5AS











*Note: Not all markings may apply to all model variations.

Available From:

Model Specified	Store#
Location	Quantity



Top Mount, Roll-In Freezers Models: PFI1, PFI2 (PFI) Roll-In

MODEL	PFI1-1AS	PFI2-5AS
EXTERNAL DIMENSIONAL DATA		
Length Overall (inches) Length Overall (mm)	33" 838	66" 1676
Depth Overall—(inches) less handle Depth Overall—(mm) less handle	33" 838	33" 838
Height Overall— (inches) less casters Height Overall— (mm) less casters	84 1/2" 2146	84 1/2" 2146
Number of doors	1	2
INTERNAL DIMENSIONAL DATA		
NET Capacity (cubic ft.) NET Capacity (Liters)	34.3 971	73.4 2079
Cart Capacity	1	2
ELECTRICAL DATA		
Volts*	115	208-230*
Full Load Amperes	10.6	10.5
REFRIGERATION DATA		
Horsepower	1/2	1
WEIGHT DATA		
Gross Weight (Crated lbs)	562	814
Gross Weight (Crated kg)	255	369









Note: Not all markings may apply to all model variations. ***Note:** 208-230 volt units are designed for field wiring.

PLAN VIEWS



