Item No.	
Quantity	



BEVERAGE-AIR

3779 Champion Blvd., Winston-Salem, NC 27105 1-888-845-9800 Fax# 1-336-245-6453 http://www.Beverage-Air.com

CUSTOMER'S CHOICE FOR A <u>HOT</u> KITCHEN Tested & Certified to Ambient Class of 100°F

3 Year Parts/Labor Warranty Additional 2 Year Compressor Warranty

SPEDP60 ELITE SERIES — STANDARD TOP WITH DRAWERS

All around prep table with enhanced refrigeration system. Improved airflow for less temperature gradient and uniform temperature distribution throughout the cabinet. Pans are cooled from the bottom, eliminating the necessity of air blanket. Airflow assures that product in open containers is kept below 41°F and above freezing. This translates into increased product shelf life, higher quality food, better food appearance, fresher product and a reduction of bacteria buildup to combat food-borne illnesses.

CABINET CONSTRUCTION

Exterior construction includes heavy-duty stainless steel finish on front, sides, top, drawers and grille. Removable hoods and insulated lid assemblies are made of matching stainless steel. Cabinet back and bottom are constructed of galvanized steel. Interior liner is made of aluminum for superior resistance to corrosion.

In cabinets with doors and drawers, doors are mounted to face of cabinet on cartridge-style hinges permitting them to self close under their own weight. Hinges also allow doors to stay open 120° and permit easy door removal for service and cleaning if required. A plug-in type vinyl magnetic gasket is attached to each door for positive seal.

Drawer frames are constructed of heavy-duty stainless steel and are supported on heavy-duty telescoping drawer slides for maximum support of stored food products. The drawer slides have a locking mechanism that prevents the drawers from being inadvertently pulled off the cabinets. Top & bottom drawers accommodate 6" deep pans. Heavy-duty pan divider supports are supplied. Foodservice pans for drawers are not included. Snap-type vinyl magnetic gasket is attached to each drawer for positive seal. Top drawer extends 17 3/4" (when opened) and bottom drawer extends 15 3/4" (when opened).

Cabinet insulation is CFC and HCFC-free foamed-in-place polyurethane of two-inch minimum thickness. Six-inch casters, 2 with brakes, are standard. Legs are available as an option.

Cutting board supplied with cabinet is 10" wide constructed of high-density white polyethylene plastic. It is readily removable for cleaning. Pans furnished for top are 4" deep and made of polycarbonate plastic. Top will hold 6" deep pans.

REFRIGERATION

More robust refrigeration system provides added capacity and efficiency. Systems are designed using CFC and HCFC-free R134a refrigerant. Recirculated, forced air from evaporator is moved under pans, which are recessed 2" from top of cabinet. Forced air over the condenser is drawn through grille under bottom drawer as well as the back and bottom of cabinet. Automatic condensate evaporator is provided to eliminate the need of floor drains.



ADDE .

*Note: Not all markings may apply to all model variations.

FOOD PREPARATION SERIES PREP TABLES SPEDP60 ELITE SERIES STANDARD TOP WITH DRAWERS

MODELS: SPEDP60



Available From:

Store#

Location

Quantity

BEVERAGE-AIR

PLAN VIEWS

29" WORKTOP

Food Prep Table — Standard Top With Drawers Models: SPEDP60

MODEL	SPEDP60-08-2	SPEDP60-08-4	SPEDP60-10-2	SPEDP60-10-4	SPEDP60-12-2	SPEDP60-12-4	SPEDP60-16-2	SPEDP60-16-4		
EXTERNAL DIMENSIONAL DATA									41 11/16"	
Length Overall (inches) Length Overall (mm)	60" 1524	OVERALL HT								
Depth Overall (inches) Depth Overall (mm)	29 1/4" 743	/								
Height Overall— (inches) Height Overall— (mm)	41 11/16" 1059									
Number of drawers	2	4	2	4	2	4	2	4	1	
Number of doors	1	-	1	-	1	-	1	-		
Top Drawer Extension (when opened)	17 3/4"	17 3/4"	17 3/4"	17 3/4"	17 3/4"	17 3/4"	17 3/4"	17 3/4"		
Bottom Drawer Extension (when opened)	15 3/4"	15 3/4"	15 3/4"	15 3/4"	15 3/4"	15 3/4"	15 3/4"	15 3/4"	+	_ 60" OVERALL WDTH .
INTERNAL DIMENSIONAL DATA									Ī	
NET Capacity (cubic ft.) NET Capacity (Liters)	17.1 484	41 11/16"								
Internal Length Overall (inches) Internal Length Overall (mm)	56" 1422		FRONT VIEW							
Internal Depth Overall (inches) Internal Depth Overall (mm)	19" 483									
Internal Height Overall—(inches) Internal Height Overall—(mm)	23" 584									
ELECTRICAL DATA										_ 60" OVERALL WIDTH
Full Load Amperes 115/60/1	9.6	9.6	9.6	9.6	9.6	9.6	9.6	9.6		
REFRIGERATION DATA										
Horsepower	1/3	1/3	1/3	1/3	1/3	1/3	1/3	1/3	41 11/16"	
WEIGHT DATA									I T	FRONT VIEW
Gross Weight (Crated lbs)	350	360	350	360	350	360	329	360	1	
Gross Weight (Crated kg)	159	163	159	163	159	163	149	163	1	





POSSIBLE PAN COMBINATION

1 FULL SIZE PAN

2 HALF SIZE PANS

6 1/6TH SIZE PANS 3 1/3RD SIZE PANS

Note: Not all markings may apply to all model variations.

DRAWER SUPPORT CAPACITY

OF PAN SUPPORTS (SUPPLIED)

2

*N/A:: Not available at time of printing.

MODEL


SPEDP60

	<u>.</u> 000	
29		
	- 61	


SPEDP60-08

1	
	provide the stand in the stand in the stand in
	•5

TOP PAN CONFIGURATIONS



SPEDP60-10



SPEDP60-12

SPEDP60-16

BEVERAGE-AIR[®] CORPORATION

3779 Champion Blvd. • Winston-Salem, NC 27105 USA • (336) 245-6400 • Fax (336) 245-6453 • (888) 845-9800 • www.beverage-air.com

Specifications are subject to change without prior notice. 04/15