

3779 Champion Blvd., Winston-Salem, NC 27105 1-888-845-9800 Fax# 1-336-245-6453 http://www.Beverage-Air.com

Commercial Refrigeration Equipment General Specification

3 Year Parts/Labor Warranty Additional 2 Year Compressor Warranty

WTR AND WTF—SERIES WORKTOP UNITS

Select from 5 standard sizes in widths of 41" (1 door), 46" (1 door), 67" (2 door), 93" (3 door), and 119" (4 door). Working height* is 35 1/2" with units installed on 6 inch casters (2 with brakes).

CABINET CONSTRUCTION

Heavy duty construction includes stainless steel on front, sides, door(s) and grille. Worktop is stainless steel with built-in back-splash. Cabinet back and bottom are galvanized steel. Interior liner is made of aluminum for longer lasting corrosion protection. Interior thermometer is standard.

Cabinets are insulated with foamed-in-place polyurethane insulation of 2" minimum thickness. Work tops are 2 1/2". Doors are mounted to cabinet on self-closing, cartridge style hinges with 120° stay open feature. Door openings include low wattage, anticondensate heaters (WTF67A only). A plug-in type vinyl magnetic gasket is attached to each door for positive seal. Convenient, contoured, pull handle is made of black anodized aluminum. Interior arrangement includes 2 steel wire epoxy coated shelves behind each door, adjustable in 1/2 inch increments.

REFRIGERATION

Balanced refrigeration systems used in all 5 sizes of self-contained refrigerated worktops provide high humidity storage of product at 35°F to 38°F. One size worktop freezer WTF67 holds product at 0°F and below. Unit is equipped with time activated, temperature terminated, electric defrost. Refrigerants include CFC-free R134a in refrigerators and 404A in freezers.

ELECTRICAL

Units wired at factory and ready for connection to a 115/60/1 phase, 15 amp dedicated outlet.

SPECIAL FEATURES

- WTR67A has earned the ENERGY STAR[®].
- 6" casters, two with brakes standard.
- Optional 6" legs or 3" casters available

*Note: Overall heights of casters may vary with different types of casters depending upon caster manufacturer designations.











WORK TOP REFRIGERATORS AND FREEZER WORKTOP FREEZER 32" BASE MODEL SERIES MODELS: WTR41 WTR46A WTR67A WTR93A WTR119A WTF67A



WTR46



WTR67A has earned the ENERGY STAR.

ELECTRICAL CONNECTION

Units pre-wired at factory and include 8' long cord and plug set.



Available From:

Model Specified	Store#
Location	Quantity



BEVERAGE-AIR

Work Top Refrigerators and Freezer

Models: WTR41, WTR46A, WTR67A, WTR93A, WTR119A, WTF67A

MODEL	WTR41	WTR46A	WTR67A	WTR93A	WTR119A	WTF67A
EXTERNAL DIMENSIONAL DATA						
Length Overall (inches) Length Overall (mm)	41" 1041	46" 1168	67" 1702	93" 2362	119" 3023	67" 1702
Depth Overall (inches) - Less handle Depth Overall (mm) - Less handle	32" 813	32" 813	32" 813	32" 813	32" 813	32" 813
Height Overall— on 6" casters (inches)* Height Overall—on 6" casters (mm)*	39 1/2" 1003	39 1/2" 1003	39 1/2" 1003	39 1/2" 1003	39 1/2" 1003	39 1/2" 1003
Depth with Door Open 90 °	55 3/8"	55 3/8"	55 3/8"	55 3/8"	55 3/8"	55 3/8"
Clear Door Opening (inches)	21 1/2" x 23 1/2	21 1/2" x 23 1/2	21 1/2" x 23 1/2"	21 1/2" x 23 1/2"	21 1/2" x 23 1/2"	21 1/2" x 23 1/2
Number of doors	1	1	2	3	4	2
INTERNAL DIMENSIONAL DATA						
NET Capacity (cubic ft.) NET Capacity (Liters)	14.75 418	16.7 473	27 765	39.8 1127	52.5 1487	27 765
Internal Length Overall (inches) Internal Length Overall (mm)	19" 483	22" 559	48" 1219	74" 1880	100 1/8" 2543	48" 1219
Internal Depth Overall (inches) Internal Depth Overall (mm)	28" 711	28" 711	28" 711	28" 711	28" 711	28" 711
Internal Height Overall (inches) Internal Height Overall (mm)	25" 635	25" 635	25" 635	25" 635	25" 635	25" 635
Number of shelves	2	2	4	6	8	4
ELECTRICAL DATA						
Full Load Amperes 115/60/1	6.3	6.3	6.3	8.6	8.6	8.6
ENERGY CONSUMPTION (KWH)	n/a	2.81	2.56	3.49	3.91	15.3
REFRIGERATION DATA						
Horsepower	1/4	1/4	1/4	1/3	1/3	3/4
WEIGHT DATA	_	_	_			
Gross Weight (Crated lbs)	295	330	420	546	675	431
Gross Weight (Crated kg)	134	150	191	248	306	196

*Note: Overall heights of casters may vary with different types of casters depending upon caster manufacturer designations.














PLAN VIEWS




WTR41



WTR46A




WTR67A



WTR93A

WTF67A



WTR119A 119" WDTH 29 1/2" 39 1/2" FRONT VIEW