



## BLCM-62-102E

Double Stack Electric Boilerless  
Combination-Oven/Steamer with  
Manual Control



*Shown on optional casters*

### OPTIONS AND ACCESSORIES (AT ADDITIONAL CHARGE)

- ☐ Additional core probe
- ☐ Casters
- ☐ Heat shield
- ☐ Wire oven rack
- ☐ Right hinge door
- ☐ Extra year warranty

### OPTIONS AND ACCESSORIES (AT NO CHARGE)

- ☐ Optional pan cassette with 2.56" (65mm) spacing

Project \_\_\_\_\_

Item No. \_\_\_\_\_

Quantity \_\_\_\_\_

- ☐ Standard pan cassette with 3.35" (85mm) spacing holds 13 sheet pans or 26 North American hotel pans
- ☐ Optional pan cassette with 2.56" (65mm) spacing holds 16 sheet pans or 32 Gastronorm pans

*Refer to operator manual specification chart for listed model names.*

### CONSTRUCTION

- 304 stainless steel exterior and interior
- Dual pane tempered viewing window with hinged inner glass for easy cleaning
- 2" (50mm) fixed drain in the bottom center of cavity
- Door mounted drip tray reduces the risk of wet, slippery floors
- Automatic door stops in positions of 110° and 180°
- Left hinge door is field convertible to the right side (with the purchase of conversion kit)
- Two step safety door latch. The first step stops the fan.

### OPERATION

- Injection steam system - water is injected onto the heating elements, the resulting steam is distributed in the oven chamber by the fan wheel
- Multiple cooking modes include hot air, combi 1 (30-40% steam), combi 2 (60-80% steam), retherming, steaming, low-temperature steaming, forced steam, and preheating
- Automated CombiWash, closed circuit cleaning system features very low water and detergent consumption and no contact with chemicals. No proprietary chemicals required, see owner's manual for detergent guidelines.
- User friendly control with dial and digital display
- Control stores up to 50 recipe programs with 10 cooking stages each
- Reversible 9 speed fan for optimum baking and roasting results
- Programmable time delay start
- 85°-480°F (30°-250°C) temperature range, 575°F (300°C) preheating
- Low water indicator

### STANDARD FEATURES

- Cassette support platform
- External core temperature probe with multiple measuring points.
- Bright halogen lights for superior visibility
- Built in hand shower
- Removeable cleaning chemical bottle shelf
- Start-up inspection service by factory authorized service agent
- One year parts and labor oven warranty\*

*\* For all international markets, contact your local distributor.*



Intertek




BLCM-62-102E

**BLODGETT OVEN COMPANY**

www.blodgett.com • 44 Lakeside Avenue, Burlington, VT 05401 • Phone: (802) 658-6600 • Fax: (802) 864-0183




## BLCM-62-102E



APPROVAL/STAMP

DIMENSIONS ARE IN INCHES (MM)



**SHORT FORM SPECIFICATIONS:** Provide Blodgett Combi model BLCM-62-102E combination-oven/steamer. The BLCM-62-102E has a pan cassette with 3.35" (85mm) rack spacing that holds 13 sheet pans or 26 North American hotel pans. The optional pan cassette with 2.5" (65mm) spacing holds 16 sheet pans or 32 Gastronorm pans. Unit shall have 304 stainless steel exterior and interior. Oven doors shall have dual pane tempered viewing window with hinged inner glass for easy cleaning. Multiple cooking modes include hot air, combi 1 (30-40% steam), combi 2 (60-80% steam), retherming, steaming, low-temperature steaming, and preheating. Unit shall have the ability to cook with pressureless steam, hot air, or combination of steam and hot air. Injection steam system - water is injected onto the heating elements, the resulting steam is distributed in the oven chamber by the fan wheel. Unit shall have bright halogen lights for superior visibility. Standard control includes user friendly digital display with dial, ability to store up to 50 recipe programs with 10 stages per recipe, and time delay start. The reversible 9 speed fan provides optimum baking and roasting results. Automated CombiWash, closed circuit cleaning system features very low water and detergent consumption and no contact with chemicals. One-year parts and labor warranty. Provide start-up inspection service by a factory authorized service agent. Provide options and accessories as indicated.

### DIMENSIONS:

**Floor space:** 44.21" x 40.51" (1122 x 1029mm)  
**Unit height:** 80.00" (2032mm)

### OVEN CLEARANCES:

*From combustible and non-combustible construction*

Right 4" (102mm)  
Left 0" (0mm)  
Back 2" (50mm)

Blodgett recommends and 12" (305mm) be maintained on the control side for servicing.

### MINIMUM ENTRY CLEARANCE (per section):

Uncrated 37.44" (951mm)  
Crated 38" (965mm)

### SHIPPING INFORMATION:

**Approx. weight:** 1020 lbs. (463 kg)

**NOTE:** The company reserves the right to make substitutions of components without prior notice

### POWER SUPPLY:

	Voltage	KW	Phase	Amperage
BLCM-62E	208 VAC	21	3	59
	240 VAC	21	3	51
	480 VAC	21	3	26
BLCM-102E	208 VAC	27	3	75
	240 VAC	27	3	65
	480 VAC	27	3	33

### WATER SUPPLY:

Good quality water feed is the responsibility of the owner. Water quality must be within the following general guidelines.

TDS: < 100 ppm Hardness: 80-120 ppm pH: 7.0 - 8.0  
Chlorides: < 30 ppm 30(min)-50(max) PSI Max. drain temp. 140°F (60°C)  
2" drain connection 3/4" garden hose cold water

The best defense against poor water quality is a water filter system designed to meet your water quality conditions. Blodgett offers optional water filters from Everpure and Terry Corp. for this unit.

Appliance is to be installed with backflow protection in accordance with Federal, State or Local codes.