

## Phoenix Heavy Duty Cheesemelters



#### OPTIONS AND ACCESSORIES (AT ADDITIONAL CHARGE)

- (AT ADDITIONAL CHARGE)
- Side splash kits (specify when ordering)
   Interconnect gas line for single gas connection for range mount units

Item No.

Quantity

<ul> <li>Model BPCM-36 - 36"</li> <li>Model BPCM-48 - 48"</li> <li>Model BPCM-54 - 54"</li> <li>Model BPCM-60 - 60"</li> <li>Model BPCM-72 - 72"</li> <li>Model BPCM-96 - 96"</li> </ul>	wide wall mounted chea wide wall mounted chea	esemelter esemelter esemelter esemelter esemelter esemelter esemelter		
Model BPCM-108 - 108	8" wide wall mounted ci	neesemeiter		
SPECIFY Gas Type	Natural Gas	Propane		
Operating altitude (if above 2000 ft (700 meters)				

### STANDARD FEATURES (All models)

- High power infrared burners
- 2" thick insulated bottom shelf
- Stainless steel front, sides, bottom and top
- 14 gauge all welded construction
- 3/4" gas pressure regulator
- Stainless steel gas tubing throughout
- One stainless steel pilot tip per burner
- Warranty: two year parts and one year labor warranty

#### STANDARD FEATURES (Wall Mount)

Wall mounting bracket

#### STANDARD FEATURES (Range Mount)


Stainless steel riser






36" WIDE UNITS SHOWN

# PHOENIX CHEESEMELTERS



APPROVAL/STAMP



FRONT VIEW

MODEL	WIDTH	DEPTH	HEIGHT	SHIPPING WEIGHT
BPCM-36RMT	36"	17-1/2"	21-1/4"	270 lbs (122 kg)
BPCM-24	24"			105 lbs (48 kg)
BPCM-36	36"			160 lbs (73 kg)
BPCM-48	48"			210 lbs (95 kg)
BPCM-54	54"			230 lbs (104 kg)
BPCM-60	60"			260 lbs (118 kg)
BPCM-72	72"			320 lbs (145 kg)
BPCM-96	96"			440 lbs (200 kg)
BPCM-108	108"			500 lbs (227 kg)

#### SHORT FORM SPECIFICATIONS

Provide Blodgett heavy duty cheesemelter. Unit to be wall or range mounted. To have high power infrared burner(s). Each burner to be furnished with one stainless steel pilot and gas tubing throughout. To be of 14 gauge all welded construction with stainless steel front, both sides and bottom. Each to be furnished with one stainless steel pilot and gas tubing throughout. Unit to be provided with a 3/4" gas regulator. Two year parts and one year labor warranty. Provide options and accessories as indicated.

UTILITY INFORMATION					
MODEL GAS RATING (BTU/hr)	OPERATING PRESSURE		GAS: Cheesemelters are supplied with 3/4" gas connection. The unit must be connect		
	(BTU/hr)	Natural Gas	Propane	with the gas regulator supplied. The gas regulator MUST be installed for proper opera-	
BPCM-36RMT	30,000		10 W.C. min. 14" W.C. max.	tion.	
BPCM-24	20,000			FLUE EXHAUST: Installation under a vented hood is recommended.	
BPCM-36	30,000				
BPCM-48	40,000				
BPCM-54	50,000	5" W.C. min.			
BPCM-60	60,000	1			
BPCM-72	70,000				
BPCM-96	80,000				
BPCM-108	90,000	1			

NOTE: The company reserves the right to make substitutions of components without prior notice

BLODGETT

www.blodgett.com 44 Lakeside Avenue, Burlington, VT 05401 • Phone: (802) 658-6600 • Fax: (802) 864-0183

NOTE: FOR COMMERCIAL USE ONLY