



Synergy Steam

40ES-KLT Short Height Electric Floor Model Tilting Kettle



OPTIONS AND ACCESSORIES (AT ADDITIONAL CHARGE)

- Etched markings
 - ☐ Gallons
 - ☐ Litres
- Strainers
 - ☐ 1/8" perforated disc strainer
 - ☐ 1/4" perforated disk strainer
 - ☐ Solid disc strainer
 - ☐ Lip strainers
- Faucets
 - ☐ Single pantry faucet
 - ☐ Double pantry faucet
- Covers
 - ☐ Lift off cover
 - ☐ Hinged cover kit
- ☐ 480 VAC, 3 phase, 60 Hz
- ☐ 2" tangent drawoff
- ☐ Basket inserts
- ☐ Pan carrier
- ☐ Kettle brush kit
- ☐ Contour measuring strip

Project _____

Item No. _____

Quantity _____

- ☐ Model 40ES-KLT - 40 gallon (151 litres) short height electric tilting floor kettle

CONSTRUCTION

- 316 stainless steel, one-piece welded construction
- Fully jacketed kettle
- All exposed surfaces shall be stainless steel
- Kettle body is sheathed in stainless steel and air gap insulated.
- ASME shop inspected, stamped and registered with the National Board for operation up to a maximum working pressure of 50 PSI.
- Outer sheathing and air insulating gap retains heat and keeps kettle exterior cooler to the touch.
- Heavy-duty stainless steel combination kettle support tilt trunnion on an enclosed base.
- Stainless steel tubular legs with adjustable bullet feet
- Heavy reinforced bar rim with a welded-in butterfly shaped pouring lip for pouring control and durability

OPERATION

- Kettle shall have an electric, self-contained steam source to provide kettle temperatures from 150°F to approximately 295°F
- Thermostatically controlled to shut off automatically when desired temperature is reached or on when temperature falls below desired setting
- Factory charged with chemically-pure water and rust inhibitors to ensure long life and minimum maintenance
- Smooth operating, self-locking tilt mechanism
- All controls shall be contained in a stainless steel enclosure within easy reach of the operator
- Thermostat
- Built in contactor
- Safety tilt cutoff
- Pilot light
- Pressure gauge
- Water level sight glass
- Safety valve
- Low water cut-off
- Heat indicator light

STANDARD FEATURES

- Faucet bracket
- Removable 1/4" perforated stainless steel strainer
- Standard voltage options
 - ☐ 208 VAC, 3 phase, 60 Hz
 - ☐ 240 VAC, 3 phase, 60 Hz
- One year parts and labor warranty*

* For all international markets, contact your local distributor.



BLODGETT

www.blodgett.com

44 Lakeside Avenue, Burlington, VT 05401 • Phone: (802) 658-6600 • Fax: (802) 864-0183

40ES-KLT SHORT HEIGHT FLOOR MODEL TILTING KETTLE

