

Camshelving® Elements Series

4-Shelf Mobile Starter Units Vented Shelf Plates with Camguard® Antimicrobial

2 Post Heights (with Casters)

70" (1778 mm), 78" (1980 mm)

3 Shelf Depths

18" (460 mm), 21" (540 mm),
24" (610 mm)

3 Shelf Depths

18" (460 mm), 21" (540 mm),
24" (610 mm)



Starter Unit includes:

4 Mobile Posts without leveling feet, pre-assembled with Post Connectors and Wedges, 1 bag of 32 Mobile Traverse Dovetails (16 ea. A and B), Vented Shelf Plates (for 4 shelves), 8 Mobile Traverses, Premium or Standard Casters (2 Swivel with Brake and 2 Swivel with no Brake) and instructions.

Features & Benefits

Strong Technology

Posts and Traverses are built using advanced manufacturing technology and the use of a non-corrosive composite material. The robust design along with unique composite material gives Elements an unprecedented longevity, durability and weight-bearing capacity in the industry. Shelves up to 60" (1530 mm) long hold up to 750 lbs. (340 kg) per unit of evenly distributed static weight. Mobile traverse features a 45° gusset for maximum cross stabilization.

Hygienic Design

Camshelving Shelf Plates contain Camguard® antimicrobial, a silver-ion technology that inhibits the growth of mold, fungus and bacteria that may cause odors, stains and product degradation. Camguard is incorporated throughout the shelf plate material so that it will never wash off or wear out. The shelf plates remove easily and can be placed in an open end Camrack® (OETR314) for washing.

Shelving for Life

Non-corrosive design will endure all areas of operation, dry-storage, coolers, warewashing, freezer and heavy condensation and humidity settings without risk of rusting, peeling, denting, cracking or warping. Functions in temperatures down to -36°F (-30°C) or warm environments up to 190°F (88°C).

Requires Minimal Assembly

Can be put together with the use of a rubber mallet. Two-piece Mobile Dovetails secure Mobile Traverses so they can be set easily into place.

Item No. _____

Specifier Identification No. _____

Model No. _____

Quantity _____



Mobile Four Shelf Unit with Vented Shelf Plates.

Flexible Design

Shelves can be easily adjusted at 4" (102 mm) increments. Add a shelf to an existing unit by simply ordering the appropriate Mobile Shelf Kit.

Optional Accessories

Identification Tags clip easily onto traverses.
Use Divider Bars to create a custom storage unit.

Premium Casters

Durable plastic body with a zinc plated post and a non-marking, thermoplastic rubber wheel. Ideal for coolers, freezers, and wet areas.

Standard Casters

Nickel plated body with a zinc plated post and a non-marking, polyurethane wheel. Recommended for dry storage.

Approvals



COMPONENT

Camshelving® Elements Series

4-Shelf Mobile Starter Units Vented Shelf Plates with Camguard® Antimicrobial

2 Post Heights (with Casters)

70" (1778 mm), 78" (1980 mm)

3 Shelf Depths

18" (460 mm), 21" (540 mm),

24" (610 mm)



3 Shelf Depths

18" (460 mm), 21" (540 mm),

24" (610 mm)

Four Shelf Starter Units with Premium Casters

CODE	TRAVERSE IN. MM	CASE LBS. (CUBE)	CASE KG. (CUBE M³)
70" (1778 mm) Height 18" (460 mm) Depth			
EMU183670V4	36" 910 mm	60.13 (5.92)	27,28 (0,17)
EMU184270V4	42" 1070 mm	64.67 (5.92)	29,33 (0,17)
EMU184870V4	48" 1220 mm	69.08 (5.92)	31,33 (0,17)
78" (1980 mm) Height 18" (460 mm) Depth			
EMU183678V4	36" 910 mm	61.41 (5.92)	27,86 (0,17)
EMU184278V4	42" 1070 mm	65.95 (5.92)	29,91 (0,17)
EMU184878V4	48" 1220 mm	70.36 (5.92)	31,91 (0,17)
70" (1778 mm) Height 21" (540 mm) Depth			
EMU213670V4	36" 910 mm	65.08 (7.39)	29,52 (0,21)
EMU214270V4	42" 1070 mm	70.57 (7.39)	31,92 (0,21)
EMU214870V4	48" 1220 mm	75.43 (7.39)	34,21 (0,21)
78" (1980 mm) Height 21" (540 mm) Depth			
EMU213678V4	36" 910 mm	66.36 (7.39)	30,10 (0,21)
EMU214278V4	42" 1070 mm	71.65 (7.39)	32,50 (0,21)
EMU214878V4	48" 1220 mm	76.71 (7.39)	34,79 (0,21)
70" (1778 mm) Height 24" (610 mm) Depth			
EMU243670V4	36" 910 mm	69.64 (8.49)	31,59 (0,24)
EMU244270V4	42" 1070 mm	75.45 (8.49)	34,22 (0,24)
EMU244870V4	48" 1220 mm	81.86 (8.49)	37,13 (0,24)
78" (1980 mm) Height 24" (610 mm) Depth			
EMU243678V4	36" 910 mm	70.92 (8.49)	32,17 (0,24)
EMU244278V4	42" 1070 mm	76.73 (8.49)	34,81 (0,24)
EMU244878V4	48" 1220 mm	83.14 (8.49)	37,71 (0,24)

Architect Specs

Posts:	Proprietary non-corrosive composite material.
Post Connectors:	Glass Filled Polypropylene.
Mobile Traverses:	Proprietary non-corrosive composite material.
Vented/Solid Shelf Plates:	Reinforced polypropylene with Camguard® antimicrobial.
Divider Bars:	Glass Filled Nylon.
Mobile Dovetails:	Resin Nylon.
Wedges:	Resin Polypropylene.

Item No. _____

Specifier Identification No. _____

Model No. _____

Quantity _____

Donut Bumper

CODE	DESCRIPTION	DIAMETER IN. (MM)	CASE LBS. (CUBE)	CASE KG. (CUBE M³)
CSMHDDDB	Donut Bumper	5" 127 mm	2.01 (0.05)	0,34 (0,001)

Case Pack: 4

Optional Accessories

Identification Tag 6"	<input type="checkbox"/> CSID6	Color: White/Clear	Case pack: 12 each
Identification Tag 3"	<input type="checkbox"/> CSID3	Color: White/Clear	Case pack: 12 each
Divider Bar Angled	<input type="checkbox"/> EDDB	Color: Speckled Gray	Case pack: 4 each
Divider Bar Straight	<input type="checkbox"/> EDBS	Color: Speckled Gray	Case pack: 4 each

Standard Color

Brushed Graphite (580)

Approvals



COMPONENT



© Cambro Manufacturing Company 5801 Skylab Road, Huntington Beach, California 92647-2056-U.S.A.
Telephone 714 848 1555 Toll Free 800 854 7631 Customer Service 800 833 3003