

## Camshelving® Elements Series

### Stationary Post Kits

#### 3 Post Heights

64" (1630 mm), 72" (1830 mm),  
84" (2140 mm)

#### 4 Shelf Depths

14" (360 mm), 18" (460 mm),  
21" (540 mm), 24" (610 mm)



#### \* Post Kit includes:

2 stationary posts with leveling feet installed,  
1 top post connector, 1 bottom post connector,  
8 post connector collar wedges (4A and 4B) in a bag  
and instructions.

### Features & Benefits

#### Strong Technology

Posts and Traverses are built using advanced manufacturing technology and the use of a non-corrosive composite material. The robust design along with unique composite material gives Elements an unprecedented longevity, durability and weight-bearing capacity in the industry. Shelves up 48" (1220 mm) long hold up to 800 lbs. (363 kg) evenly distributed static weight. Shelves 54" – 78" (1380 mm – 1980 mm) long hold up to 600 lbs. (272 kg) each. Shelves connected by Corner Connectors hold up to 400 lbs. (182 kg) on a 36" (910 mm) to 48" (1220 mm) traverse.

#### Hygienic Design

Camshelving Shelf Plates contain Camguard® antimicrobial, a silver-ion technology that inhibits the growth of mold, fungus and bacteria that may cause odors, stains and product degradation. Camguard is incorporated throughout the shelf plate material so that it will never wash off or wear out. The shelf plates remove easily and can be placed in an open end Camrack® (OETR314) for washing.

#### Shelving for Life

Non-corrosive design will endure all areas of operation – dry-storage, coolers, warewashing, freezer and heavy condensation and humidity settings – without risk of rusting, peeling, denting, cracking or warping. Functions in temperatures down to -36°F (-30°C) or warm environments up to 190°F (88°C).

#### Fits in Any Space

Innovative design helps maximize valuable space and provides strength and stability. Straight line components are attached by sharing posts of existing units with no loss of weight-bearing capacity. Corner Connectors bring units together in 90° angle to create corner & U-shaped units. Reduces costs by sharing posts of existing unit without the use of add-on clips or "S" hooks.

#### Requires Minimal Assembly

Can be put together with the use of a rubber mallet. Two-piece dovetails secure Traverses so they can be set easily into place.

Item No. \_\_\_\_\_

Specifier Identification No. \_\_\_\_\_

Model No. \_\_\_\_\_

Quantity \_\_\_\_\_



Four Shelf Unit with Vented Shelf Plates.

Post Kit includes two Posts, one set of Post Connectors, and a bag of 8 Post Connector Wedges.

#### Flexible Design

Shelves can be easily adjusted at 4" (102 mm) increments. Add a shelf to an existing unit by simply ordering the appropriate Shelf Kit. Adjustable foot on bottom of each stationary Post adjusts easily for floor irregularities so shelf contents are securely stored and leveled.

#### Optional Accessories

Includes Wall Fastener and Seismic Foot. Each are packed 4 per case. Identification Tags clip easily onto traverses.

### Approvals



COMPONENT

\* Does not include Wall Fastener and Seismic Foot.

# Camshelving® Elements Series

## Stationary Post Kits

### 3 Post Heights

64" (1630 mm), 72" (1830 mm),  
84" (2140 mm)

### 4 Shelf Depths

14" (360 mm), 18" (460 mm),  
21" (540 mm), 24" (610 mm)



Item No. \_\_\_\_\_

Specifier Identification No. \_\_\_\_\_

Model No. \_\_\_\_\_

Quantity \_\_\_\_\_

### \* Post Kit includes:

2 stationary posts with leveling feet installed,  
1 top post connector, 1 bottom post connector,  
8 post connector collar wedges (4A and 4B) in a bag  
and instructions.

### Stationary – Post Kits

CODE	DEPTH IN. (MM)	HEIGHT IN. (MM)	CASE LBS. (CUBE)	CASE KG. (CUBE M³)
EPK1464	14" 360 mm	64" 1630 mm	8.42 (0.46)	3,82 (0,01)
EPK1864	18" 460 mm	64" 1630 mm	8.66 (0.46)	3,93 (0,01)
EPK2164	21" 540 mm	64" 1630 mm	8.84 (0.46)	4,00 (0,01)
EPK2464	24" 610 mm	64" 1630 mm	9.02 (0.46)	4,08 (0,01)
EPK1472	14" 360 mm	72" 1830 mm	9.27 (0.52)	4,20 (0,01)
EPK1872	18" 460 mm	72" 1830 mm	9.50 (0.52)	4,31 (0,01)
EPK2172	21" 540 mm	72" 1830 mm	9.68 (0.52)	4,39 (0,01)
EPK2472	24" 610 mm	72" 1830 mm	9.86 (0.52)	4,47 (0,01)
EPK1484	14" 360 mm	84" 2140 mm	10.49 (0.61)	4,76 (0,02)
EPK1884	18" 460 mm	84" 2140 mm	10.72 (0.61)	4,86 (0,02)
EPK2184	21" 540 mm	84" 2140 mm	10.90 (0.61)	4,94 (0,02)
EPK2484	24" 610 mm	84" 2140 mm	11.08 (0.61)	5,02 (0,02)

### Corner Connector Set

CODE	DESCRIPTION	CASE LBS. (CUBE)	CASE KG. (CUBE M³)
ECC1	Right and Left	0.70 (0.04)	0,32 (0,001)

Case Pack: 1 set

## Architect Specs

**Posts:** Proprietary non-corrosive composite material.  
**Post Connectors:** Glass Filled Polypropylene.  
**Traverses:** Proprietary non-corrosive composite material.  
**Vented/Solid Shelf Plates:** Reinforced polypropylene with Camguard® Antimicrobial.  
**Corner Connectors:** Glass Filled Polypropylene.  
**Adjustable Foot:** Glass Filled Nylon.  
**Seismic Foot:** Stainless steel post and wide foot plate, 3 holes for bolts.  
 (Bolts not provided).  
**Divider Bars:** Glass Filled Nylon.  
**Wall Fastener:** Stainless Steel.  
**Dovetails:** Resin Nylon.  
**Wedges:** Resin Polypropylene.

## Optional Accessories

**Seismic Foot**  CSEQ3 **Color:** Silver **Case pack:** 4 each  
 (Bolts not provided)  
**Wall Fastener**  CSWF **Color:** Silver **Case pack:** 4 each  
**Identification Tag 6"**  CSID6 **Color:** White/Clear **Case pack:** 12 each  
**Identification Tag 3"**  CSID3 **Color:** White/Clear **Case pack:** 12 each

## Standard Color

Brushed Graphite (580)

## Approvals



COMPONENT

\* Does not include Wall Fastener and Seismic Foot.



© Cambro Manufacturing Company 5801 Skylab Road, Huntington Beach, California 92647-2056-U.S.A.  
 Telephone 714 848 1555 Toll Free 800 854 7631 Customer Service 800 833 3003