CADDY Food Service Systems

page 1 of 1

Self-leveling Dispensers for Plates, Bowls, & Saucers (Unheated)




PROJECT:

LOCATION:



CM-S-102 to CM-S-502



CM-S-103 to CM-S-503



CM-SQ-103 to CM-SQ-503



CM-S-104 to CM-S-504

Two Dispenser Capacity up to 144 plates or 72 bowls **						
Model	Dish/l	3ow	Dia.	Length	Width	Height
CM-S-102	up	to	$5\frac{3}{4}$ "	23 ½"	16"	34" *
CM-S-202	5 ⁷ / ₈ "	to	7 <u>1</u> "	23 ½"	16"	34" *
CM-S-302	7 3 "	to	9 ½"	29 ¹ / ₄ "	16"	34" *
CM-S-402	9 5 "	to '	10 1 "	29 ¹ / ₄ "	16"	34" *
CM-S-502	10 ½"	to	12"	33"	16 ½"	34" *

CM-S-502	10 ¹ / ₄ "	to	12"	33"	16 ½"	34" *
Three Dispens	Three Dispenser Capacity up to 216 plates or 108 bowls **					
Model	Dish/	Bov	vl Dia.	Length	Width	Height
CM-S-103	up	to	5 ³ / ₄ "	35 ½"	16"	34" *
CM-S-203	5 ⁷ / ₈ "	to	7 ½"	35 ½"	16"	34" *
CM-S-303	7 3 "	to	9 <u>1</u> "	43 ⁷ / ₈ "	16"	34" *
CM-S-403	9 5 "	to	10 ½"	43 ⁷ / ₈ "	16"	34" *

49 ½"

 $16\frac{1}{2}$ "

Three Dispenser Capacity up to 216 plates or 108 bowls **					
Model	Dish/Bowl Dia.	Length	Width	Height	
CM-SQ-103	up to $5\frac{3}{4}$ "	23 ½"	23 ½"	34" *	
CM-SQ-203	$5\frac{7}{8}$ " to $7\frac{1}{4}$ "	23 ½"	23 ½"	34" *	
CM-SQ-303	$7\frac{3}{8}$ " to $9\frac{1}{2}$ "	29 1 "	29 1 "	34" *	
CM-SQ-403	$9\frac{5}{8}$ " to $10\frac{1}{8}$ "	29 ¹ / ₄ "	29 ¹ / ₄ "	34" *	
CM-SQ-503	$10\frac{1}{4}$ " to 12"	33"	33"	34" *	

Four Dispenser Capacity up to 288 plates or 144 bowls **						
Model	Dish/l	Зоч	/l Dia.	Length	Width	Height
CM-S-104	up	to	5 ³ / ₄ "	23 ½"	23 ½"	34" *
CM-S-204	5 ⁷ / ₈ "	to	7 1 "	23 ½"	23 ½"	34" *
CM-S-304	7 3 "	to	9 <u>1</u> "	29 1 "	29 1 "	34" *
CM-S-404	9 <u>5</u> "	to	10 ½"	29 1 "	29 1 "	34" *
CM-S-504	10 ½"	to	12"	33"	33"	34" *

Height excludes flange & guide posts. Add 3 ¹/₄" for overall height.
** Actual capacities vary with shape of object to be dispensed.

CM-S-503

Caddymagic self-leveling dispenser to be Caddy Corporation model CM-

Unit to have 16 gauge stainless steel top with 2" turned down channel edge on 4 sides and welded finished corners. Exterior of cabinet to be finished in stainless steel.

Self-leveling cylinders to be field adjustable without the use of tools for china and plastic dishes without requiring prior identification, irrespective of weight, height, or brand. Calibrating mechanism to have multiple extension springs peripherally suspended from a circular storage bank. Selective engaging of springs with dish carrier assembly to permit balancing and dispensing of any load within range of model selected. Cylinders to have 18 gauge stainless steel raised top flange, in high luster finish, with three 3" high plastic guide posts equally spaced.

Bottom of cabinet to be 12 gauge stainless steel, rust resistant metal and body to have full height vertical plastic corner bumpers. Casters are to be 4" diameter swivel type with polyurethane tires.

Unit to be provided with the following accessories:

Accessories

	ACC-63 - 5" diameter swivel caste	rs with polyurethane tire:
	in lieu of 4" diameter swivel casters	s. (Add 1 $\frac{1}{8}$ " to height)
_	•	

ACC-41 - Caster brakes on two diagonal casters.

ACC-50 - Perimeter bumpers with replaceable corner bumpers. (Add 1 $\frac{1}{4}$ " to length and width)

 \square ACC-52 - Vertical corner bumpers only. Easy to replace. (Add 1 $\frac{1}{4}$ " to length and width)



CADDY CORPORATION

509 Sharptown Road P.O. Box 345 Bridgeport, NJ 08014-0345 Tel: 856-467-4222 Fax: 856-467-5511

General Specifications