CADDY Food Service Systems

page 1 of 1


Self-leveling Dispensers Open Tubular Style for


Plates, Bowls, & Saucers (Unheated)



PROJECT:

LOCATION:







CM-TQ-103 to CM-TQ-503



CM-T-104 to CM-T-504

Two Dispense	Two Dispenser Capacity up to 144 plates or 72 bowls **							
Model	Dish/E	Зow	l Dia.	Length	Width	Height		
CM-T-102	up	to	$5\frac{3}{4}$ "	26 ³ / ₄ "	15 ³ / ₈ "	37"		
CM-T-202	5 7 /8"	to	7 1/4"	26 ³ / ₄ "	15 ³ / ₈ "	37"		
CM-T-302	7 3 "	to	9 ½"	32 ½"	17 ½"	37"		
CM-T-402	9 <u>5</u> "	to	10 1 "	32 ½"	17 ½"	37"		
CM-T-502	10 ½"	to	12"	36 ¹ / ₄ "	19"	37"		

Three Dispense	penser Capacity up to 216 plates or 108 bowls **							
Model	Dish/Bowl Dia.			Length	Width	Height		
CM-TQ-103	up	to	$5\frac{3}{4}$ "	26 ³ / ₄ "	25 ³ / ₄ "	37"		
CM-TQ-203	5 7 /8"	to	7 ½"	26 ³ / ₄ "	25 ³ / ₄ "	37"		
CM-TQ-303	7 3 "	to	9 ½"	32 ½"	31 ½"	37"		
CM-TQ-403	9 <u>5</u> "	to	10 ½"	32 ½"	31 ½"	37"		
CM-TQ-503	10 ½"	to	12"	36 ¹ / ₄ "	35 ½"	37"		

Three Dispenser Capacity up to 216 plates or 108 bowls **							
Model	Dish/Bowl Dia.			Length	Width	Height	
CM-T-103	up	to	$5\frac{3}{4}$ "	38 <u>1</u> "	15 ³ / ₈ "	37"	
CM-T-203	5 ½"	to	7 1 "	38 1 "	15 ³ / ₈ "	37"	
CM-T-303	7 3 "	to	9 <u>1</u> "	46 ⁷ / ₈ "	17 ¹ / ₈ "	37"	
CM-T-403	9 <u>5</u> "	to	10 ½"	46 ⁷ / ₈ "	17 ½"	37"	
CM-T-503	10 ½"	to	12"	52 ½"	19"	37"	

Four Dispenser Capacity up to 288 plates or 144 bowls **							
Model	Dish/l	3ow	Dia.	Length	Width	Height	
CM-T-104	up	to	$5\frac{3}{4}$ "	26 ³ / ₄ "	25 ³ / ₄ "	37"	
CM-T-204	5 ⁷ / ₈ "	to	7 <u>1</u> "	26 ³ / ₄ "	25 ³ / ₄ "	37"	
CM-T-304	7 3 "	to	9 <u>1</u> "	32 ½"	31 ½"	37"	
CM-T-404	9 <u>5</u> "	to ´	10 1 "	32 ½"	31 ½"	37"	
CM-T-504	10 ½"	to	12"	36 ¹ / ₄ "	35 ½"	37"	

^{**} Actual capacities vary with shape of object to be dispensed.

General Specifications

Caddymagic self-leveling dispenser to be Caddy Corporation model CM-_____.

Unit to have 16 gauge stainless steel reinforced top and 1" O.D. 16 gauge stainless steel tubular frame of all welded construction with stainless steel cross bracing on four sides. Casters to be 4" diameter heavy-duty swivel type with $\frac{3}{4}$ " stems and polyurethane tires.

Self-leveling cylinders to be field adjustable without the use of tools for china and plastic dishes without requiring prior identification, irrespective of weight, height, or brand. Calibrating mechanism to have multiple extension springs peripherally suspended from a circular storage bank. Selective engaging of springs with dish carrier assembly to permit balancing and dispensing of any load within range of model selected. Each cylinder to have a 20 gauge stainless steel. enclosure and 18 gauge stainless steel raised top flange, in high luster finish, with three 3" high plastic guide posts equally spaced.

Unit to be provided with the following accessories:

Accessories

ACC-63 - 5" diameter swivel casters with	n polyurethane
tires in lieu of 4" diameter swivel casters height)	. (Add 1 $\frac{1}{8}$ " to

П	ACC-38	- Circular	bumpers	(Add 4" to	length ar	nd width)

