# **CADDY** Food Service Systems

page 1 of 1




## **Dish Caddys** Single Compartment





PROJECT:

LOCATION:

Dish & Tray Caddys are designed to make storing, moving, and dispensing dishes easy. At less than 31" high, they can store under counters or serving tables requiring no extra floor space. Fold away covers permit access to dishes from the top as well as the front of each unit.







1-1	30
T-1	40

T-145

TH-130 TH-140

Dimensions			Plate Qty.*				
Model	Length	Width	Height	9"	7"	6"	5"
T-130, T-135 TH-130	25 ½"	15 <sup>3</sup> / <sub>4</sub> "	30"	80	120	120	160
T-140, T-145 TH-140	35 ½"	15 <sup>3</sup> / <sub>4</sub> "	30"	120	160	200	240

<ul> <li>Actual capacities</li> </ul>	vary with	shape of	object to b	e dispensed.
---------------------------------------	-----------	----------	-------------	--------------

Electrical Data			NEMA			
Model	Volts	φ	Amps	Plug	Outlet**	
TH-130 TH-140	120		4.1	5-15P	5-15R	
	208	1	2.4	5-15P	5-15R	
	240		2.0	5-15P	5-15R	

Outlet not supplied by Caddy Corporation.

### **General Specifications**

Dish Caddy to be Caddy Corporation model

Unit to be constructed of 16 gauge stainless steel with rounded coved corner interior. Frame to be 1" O.D. 16 gauge stainless steel tubing and fitted with 4" diameter heavy-duty swivel type casters with  $\frac{3}{4}$ " stems and polyurethane tires. Stainless steel spacers to be between tubular frame and body to eliminate dirt pockets. Sides to have continuous neoprene bumpers set into stainless steel channel frames. All stainless steel to be type 304 with No. 4 finish and be all welded construction.

Continue for

#### **Enclosed Model Specifications:**

Dish Caddy to be fitted with folding covers, for sanitary dish storage, of  $\frac{1}{8}$ " thick fiberglass reinforced plastic, fastened with 16 gauge stainless steel hinges. Covers furnished with self-operating positive locking clips. Covers shall not protrude beyond frame of unit when in open position.

Continue for

#### **Heated Model Specifications:**

Heating element to be 500 watts, mounted under plate storage compartments. Heating element and wiring to be completely concealed. Electrical control box to be stainless steel and installed for easy removal for service. Control box to include infinite Hi-Lo heat control for temperature settings 1 through 9 and a recessed male three-pronged NEMA twist-lock receptacle. Unit to be supplied with a 6'-0" long cord with a NEMA twist-lock female connector.

Heated units only to be



Unit to be provided with the following accessories:

#### Accessories

Partitions - Adjustable stainless steel sliding partitions hold dishes in place and reduce noise; especially desirable for use with bowls, irregularly shaped dishes or for use over ramps or rough floors. Partitions hand-adjust to any size dish, may be completely moved to either end or removed to provide full open compartment.

ACC-33\*\*\* - Four compartment partition set.

ACC-25\*\*\*\* - Three compartment partition set.

**ACC-35\*\*\*\*** - Four compartment partition set.

ACC-38 - Circular bumpers. (Add 4" to length and width)

\*\*\* To be used with model #T-130, T-135, & TH-130 \*\*\*\* To be used with model #T-140, T-145, & TH-140



## CADDY CORPORATION

Bridgeport, NJ 08014-0345 Tel: 856-467-4222 Fax: 856-467-5511

internet: www.caddycorp.com