

Dunnage Racks

Tubular/Channel Arch

ALUMINUM CONSTRUCTION

Item No. _____

Quantity _____

Job Name _____

Spec No. _____

Applications: Ideal for any storage application. Dunnage racks keep product organized and off of the floor. Prolongs product life by circulating air underneath. 12" height off the ground meets all sanitary health codes. Approved for use in freezers, displays, general storage, and warehouse areas.

Construction: Heavy duty, high tensile extruded aluminum. Type 6063-T5 alloy. All heli-arc welded construction. Features a lifetime guarantee against rust. Aluminum offers a high level of displacement strength with the added benefit of low weight for safe and easy moving in clean-up projects. Shipped assembled for immediate use.

ED - Series: Tubular construction with 1-1/2" X 1-3/4" high tensile aluminum tubing. Sturdy straight tubular legs. 2,200lb. distributed weight capacity.

CA - Series: Top channel arch 2-7/8" construction with solid high tensile aluminum. Sturdy straight 1-1/2" tubular legs. 2,500lb. distributed weight capacity. Units over 5' long have 3 sets of legs.

TUBULAR DUNNAGE RACK

Model	H	W	D	Weight
328ED	12"	36"	20"	10
329ED	12"	48"	20"	13
330ED	12"	60"	20"	14
332ED	12"	36"	24"	11
333ED	12"	48"	24"	15
334ED	12"	60"	24"	17

CHANNEL ARCH DUNNAGE RACK

Model	H	W	D	Weight
328CA	12"	36"	18"	9
329CA	12"	48"	18"	12
330CA	12"	60"	18"	14
331CA	12"	72"	18"	18
332CA	12"	36"	24"	12
333CA	12"	48"	24"	16
334CA	12"	60"	24"	18
335CA	12"	72"	24"	23

Add /8 for 8" height.

/PC5A HD Caster Option

Custom Sizes
Available



CHANNEL
MANUFACTURING, INC.

55 Channel Drive • Port Washington, NY 11050-2216
8891 NW 102nd Street • Medley, FL 33178
Tel: 516-944-6271 • Fax: 516-944-0625
Toll Free: 866-712-7283

www.channelmfg.com • Email: sales@channelmfg.com