REACH-IN REFRIGERATOR

Product Specifications

1RES - Extra Wide Refrigerator Shallow Depth

Solid Door, Self-Contained

Units available in one, two and three sections. All upright models contain 3" non-CFC polyurethane foam insulation. Our selection of Reach-In Refrigerators are available in standard depth, Shallow Depth, Slim Line and Extra Wide models.



OPTIONS AND ACCESSORIES

Stainless steel case back	 Half doors
Increased refrigeration systems	Pass-Thru
Stainless steel shelves	Remote models
Digital thermometer	Standard depth
Rehinging of doors (consult factory)	Hinged glass doors
Expansion valve system	Special electrical requirements (consult factory)

Adjustable Legs

Consult factory for other model configurations, options and accessories.



Toll-Free: 800-523-7138 Phone: 215-244-1400 Fax: 215-244-9579

539 Dunksferry Road Bensalem, PA 19020 www.continentalrefrigerator.com

DIMENSIONAL DATA	
Net Capacity (cu. ft.)	18 (510 cu l)
Width, Overall (in.)	281/2 (724 mm)
Depth, Overall (incl. handles) (in.)	29 ¹ / ₄ (743 mm)
Depth [less door(s)] (in.)	257/8 (657 mm)
Depth [door(s) open 90°] (in.)	49 ¹ / ₂ (1257 mm)
Clear Door Width (in.)	217/8 (556 mm)
Clear Full Door Height. (in.)	585/8 (1489 mm)
Clear Half Door Height. (in.)	27 ¹ / ₂ (699 mm)
Height, Overall (incl. 5" casters) (in.)	821/4 (2089 mm)
No. of Full Door(s)	1
No. of Half Door(s)	2
No. of Shelves	3
Shelf Area (sq. ft.)	20.4 (1.9 sq m)
REFRIGERANT DATA	
Condensing Unit Size (H.P.)	1/4
Capacity (BTU/Hr)*	1940
ELECTRICAL DATA	
Cabinet	115/60/1
Feed Wires (incl. ground)	3
Condensing Unit	115/60/1
Total Amps	6.9
Cabinet Amps	1.6
SHIPPING DATA	
Height - Crated (in.)	85 ¹ / ₂ (2172 mm)
Width - Crated (in.)	315/8 (803 mm)
Depth - Crated (in.)	42 (1067 mm)
Volume - crated (cu. ft.)	65 (1841 cu l)
Weight Standard - Crated (lbs.)	310 (141 kg)
Weight SS - Crated (lbs.)	370 (168 kg)

* Rating @ +25°F evaporator, 90°F ambient Figures in parentheses reflect metric equivalents.

Weight Standard - Uncrated (lbs.)

Weight SS - Uncrated (lbs.)

IMPORTANT NOTE: If the cabinet is located directly against a wall and/or under a low ceiling, a minimum clearance of 12" is required.

210 (95 kg)

270 (122 kg)

Project Name: Model Specified: Location: Item No: Quantity:		
Location:	Project Name:	
Location:		
Location:	Model Specified:	
	·	
Item No: Quantity:	Location:	
Item No: Quantity:		
	Item No:	Quantity:
APPROVAL:	APPROVAI ·	
711 110 7712	, , , , , , , , , , , , , , , , , , ,	

Standard Design Features

REACH-IN REFRIGERATOR

REFRIGERATION SYSTEM

Environmentally-safe R-134a refrigerant

CABINET ARCHITECTURE

3" non-CFC polyurethane foam insulation

Chrome-plated flow line handle

Cam action, lift off hinges

Self-closing door

Magnetic snap-in door gasket

Cylinder lock in door

5" casters

Heavy-duty epoxy-coated steel shelves

MODEL FEATURES

Automatic interior lighting

External dial thermometer

Automatic, energy-saving, electric condensate evaporator

FLECTRICAL

Completely pre-wired at factory for connection to 115/60/1 phase, 15 amp dedicated outlet $\,$

10 ft. cord and plug set included, 90° plug

STANDARD

Stainless steel front, aluminum end panels and interior

SHEEK SA

Stainless steel exterior, aluminum interior

SUFFIX SS

Stainless steel exterior and interior



Equipped with one NEMA-5-15P Plug





This Continental Refrigerator product is warranted to be free from all manufacturing defects, material or workmanship, for a period of one (1) year from date of original installation, or fifteen (15) months from date of shipment, whichever occurs first. All motor-compressor assemblies are warranted to be free from defects, material and workmanship, for a period of five (5) years from date of installation.

Due to our continued efforts in developing innovative products, specifications subject to change without notice.









© Copyright 2011. Continental Refrigerator. A Division of National Refrigeration & Air Conditioning Products, Inc.

1RES - Extra Wide Refrigerator Shallow Depth Model Blueprint



FRONT VIEW



RIGHT VIEW



Toll-Free: 800-523-7138 Phone: 215-244-1400 Fax: 215-244-9579

539 Dunksferry Road Bensalem, PA 19020 www.continentalrefrigerator.com