# Continental Refrigerator

## EXTRA-WIDE SLIDING GLASS DOOR DISPLAY REFRIGERATOR

#### Utilizing Environmentally Safe, CFC-free R-134a Refrigerant



### **Standard Features**

- Modern, State-of-the-Art Styling Performance Rated Refrigeration System Utilizing Environmentally Safe R-134a Refrigerant
- 3" Non-CFC Polyurethane Foam Insulation
- Self-Closing Doors
- Cylinder Lock in Each Door
- Automatic Electric Condensate Evaporator
- 5" Casters
- Heavy Duty, Epoxy-Coated Steel Shelves
- External Dial Thermometer
- Double-Pane, Tempered Sliding Glass Doors
- · Fluorescent Interior Lighting

Standard (S/S Front, Aluminum End Panels & Interior Suffix SA (S/S Exterior, Aluminum Interior Suffix SS (S/S Exterior & Interior)

#### **Optional Features & Accessories**

- Half Door
- Pass-Thru (Glass One Side Only)
- Remote
- Shallow Depth
- Leas
- Stainless Steel Case
   Back
- Extra ShelvesStainless Steel
- Shelves
  Digital Thermometer
- Increased Refrigeration Systems




SPECIFICATIONS DIMENSIONAL DATA	2RE-SGD Reach-In	2RE-SGD-PT Pass-Thru (GLASS ONE SIDE ONLY)
Net Capacity (cu. ft.) Width, Overall (in.) Depth, Overall (Incl. Hdls.) (in.) Depth (Less Door(s) (in.) Clear Door Width (in.) Clear Full-Door Height (in.) Clear Half-Door Height (in.) Height, Overall (Incl. 5" Casters) No. of Full Door(s) No. of Half Door(s) No. of Shelves Shelf Area (sq. ft.) Tray Slide Capacity (Half)	50 57 34 32 21 <sup>7</sup> / <sub>8</sub> 58 <sup>1</sup> / <sub>4</sub> 27 82 <sup>1</sup> / <sub>4</sub> 2 4 8 40.8 12 ea.	50 57 36 32 21 <sup>7/s</sup> 58 <sup>1</sup> /4 27 82 <sup>1</sup> /4 4 8 8 8 8 40.8 12 ea.
Tray Slide Capacity (Full) <b>REFRIGERATION DATA</b> Condensing Unit Size (H.P.) Capacity (BTU/Hr)*	24 ea. ½ 4010	24 ea. ½ 4010
ELECTRICAL DATA Cabinet Specifications Feed Wires (Incl. Ground) Condensing Unit Specs. Total Amperes Cabinet Amperes Defrost Amperes Power Supply Cord	115/60/1 3 115/60/1 13.6 4.1 - yes	115/60/1 3 115/60/1 14.3 4.8 - yes
SHIPPING DATA Height – crated (in.) Width – crated (in.) Depth – crated (in.) Volume – crated (cu.ft.) Weight Std – crated (lbs.) Weight SS – crated (lbs.) Weight Std – uncrated (lbs.) Weight SS – uncrated (lbs.)	81½ 55 37 97 530 610 360 440	81½ 55 37 97 610 680 430 510

\* Rating @ +25°F Evaporator, 90° Ambient

Note: All specifications subject to change without notice.

Note: If the cabinet is located directly against wall and/or under low ceiling, a minimum clearance of 12" is required.







A Division of National Refrigeration & A/C Products, Inc. 539 Dunksferry Road Bensalem, PA 19020 (800) 523-7138 Fax: (215) 244-9579 www.continentalrefrigerator.com