

# BACK BAR EQUIPMENT

**Model: BBC69S**

## 69" Back Bar Cooler - Shallow Depth

Textured baked enamel finish (black) exterior with all stainless steel countertop, heavy-duty galvanized interior with reinforced stainless steel floor.

**Designed to maintain NSF-7 temperatures in 100°F ambient.**



### Options and Accessories

(upcharge and lead times may apply)

Stainless steel exterior (-SS models)	Wine rack
Food storage rated stainless steel interior (NSF-7)	Remote models
Glass doors in lieu of solid doors	Expansion valve system
Add'l epoxy-coated shelves with clips	Casters or legs
Stainless steel shelves with clips	Standard depth
Automatic, electric condensate evaporator	Pass-thru
Condensing unit on right	

Project Name:

Model Specified:

Location:

Item No:

Quantity:

AIA #:

SIS #:

### Standard Model Features

#### REFRIGERATION SYSTEM

Performance-rated **front breathing** refrigeration system  
 Environmentally-safe R-134a refrigerant  
 Full length, extra large coil  
 Automatic, energy-saving, non-electric condensate evaporator

#### CABINET ARCHITECTURE

High density, non-CFC polyurethane foamed-in-place insulation  
 Heavy-duty, epoxy-coated steel shelves  
 Magnetic snap-in gasket (each door)  
 Cylinder-keyed security lock (each door)  
 Stainless steel reinforced threshold

#### MODEL FEATURES

Easily accessible and serviceable slide-out condensing unit  
 Removable front, rear and side venting louvered panels  
 Interior light

**Continental**  
 Refrigerator

Toll-Free: 800-523-7138  
 Phone: 215-244-1400  
 Fax: 215-244-9579

539 Dunksferry Road  
 Bensalem, PA 19020  
[www.continentalrefrigerator.com](http://www.continentalrefrigerator.com)

APPROVAL:

## Model Specifications

### DIMENSIONAL DATA

Net Capacity (cu. ft.)	18 (510 cu l)
Width, Overall (in.)	69 (1753 mm)
Depth, Overall (in.) (incl. handles & bumpers)	25 1/4 (641 mm)
Depth, Body Only (in.) (less doors)	21 (533 mm)
Height, Overall (in.) (not incl. columns)	36 3/4 (933 mm)
No. of Doors	2
No. of Shelves	4

### REFRIGERANT DATA

Condensing Unit Size (H.P.)	1/3
Capacity (BTU/Hr)*	2250

### ELECTRICAL DATA

Voltage (int'l)	115/60/1 (220/50/1)
Feed Wires (incl. ground)	3
Total Amps (int'l)	6.7 (5.0)
10 ft. Cord/Plug [attached] (int'l)	Yes (No)

### SHIPPING DATA



Weight (lbs.)	415 (188 kg)
Height - Crated (in.)	46 (1168 mm)
Width - Crated (in.)	78 (1981 mm)
Depth - Crated (in.)	42 (1067 mm)

\* Rating @ +25°F evaporator, 90°F ambient  
Figures in parentheses reflect metric equivalents rounded to the nearest whole unit.



Equipped with one NEMA-5-15P Plug  
(varies by country)

## Model Plan Views



**Continental**  
Refrigerator

Toll-Free: 800-523-7138  
Phone: 215-244-1400  
Fax: 215-244-9579

539 Dunkserry Road  
Bensalem, PA 19020  
[www.continentalrefrigerator.com](http://www.continentalrefrigerator.com)

Due to our continued efforts in developing innovative products, specifications subject to change without notice.



Intertek



MADE IN THE U.S.A.

© Copyright 2015. Continental Refrigerator.  
A Division of National Refrigeration & Air Conditioning Products, Inc.