## BASE MODEL SANDWICH UNIT

Model: CRA43-6

# 43" Standard Top Sandwich Unit Refrigerator with Solid Doors - 6 Pans

Heavy gauge #300 Series stainless steel top, stainless steel front and end panels, galvanized steel rear and grils and aluminum interior. Certified under NSF-7 to maintain temperatures in 86°F ambient and designed to maintain NSF-7 temperatures in 100°F ambient.



### **Options and Accessories**

(upcharge and lead times may apply)

(aponargo ana load timos may appry)		
Drawers in lieu of door	Stainless steel pan slides	
Drawer section above the condensing unit*	Expansion valve system	
Overshelves (single or double)	Stainless steel shelves	
Condensing unit left or right	Flat insulated night cover	
Additional epoxy-coated steel shelves	Remote models	
Automatic, electric condensate evaporator	Door locks	
Exterior dial or digital thermometer	Adjustable legs	
Rear-mounted cutting board	Crumb catcher	
Stainless steel back and interior	Front breathing	

<sup>\*</sup>Drawer section above condensing unit holds (1) 12 x 20 x 6 pan



**Toll-Free: 800-523-7138** Phone: 215-244-1400 Fax: 215-244-9579

539 Dunksferry Road Bensalem, PA 19020 www.continentalrefrigerator.com **Project Name:** 

**Model Specified:** 

Location:

Item No: Quantity:

AIA #: SIS #:

### **Standard Model Features**

### REFRIGERATION SYSTEM

Performance-rated refrigeration system

Environmentally-safe R-134a refrigerant

Unique air flow distribution allows pan product to maintain 33° - 41°F

Automatic, energy saving, non-electric condensate evaporator

Non-corrosive, plasticized fin evaporator coil

Easily serviceable, slide-out condensing unit

### **CABINET ARCHITECTURE**

2" non-CFC polyurethane foam insulation

Spring loaded, self closing doors

Magnetic snap-in door gaskets

Heavy-duty, epoxy-coated steel shelves

12" deep, full length nylon cutting board

Insulated lid

5" casters

Completely enclosed, vented and removable rear and side grills

Refrigerated door section above the condensing unit

### **MODEL FEATURES**

(6) 1/6 size non-recessed pans, 4" deep

Interior hanging thermometer

Field rehingeable doors

<u>NOTE</u>: CRA models come standard with a door over the condensing unit. A drawer over the condensing unit is an option.

APPROVAL:

IVIO	aei Si	oecm	ication

DIMENSIONAL DATA	
Net Capacity (cu. ft.)	12 (340 cu I)
1/6 Size Pans (4" deep)	6
Width, Overall (in.)	43 (1092 mm)
Depth, Overall (in.) (incl. handles & bumpers)	36 1/16 (916 mm)
Depth, Cutting Board (in.)	12 (305 mm)
Height, Overall (in.) (incl. 5" casters)	42 (1067 mm)
Shelf Area (sq. ft.)	5.6 (.5 sq m)
No. of Shelves	2
No. of Full Doors	1
No. of Half Doors	1
Interior Depth (in.)	30 (762 mm)
Interior Height (in.)	26 (660 mm)
Interior Height (in.) (above condenser)	12 1/2 (318 mm)
Interior Width (in.)	39 (991 mm)

### **REFRIGERANT DATA**

Condensing Unit Size (H.P.)	1/4	
Capacity (BTU/Hr)*	2000	

### **ELECTRICAL DATA**

Voltage (int'l)	115/60/1 (220/50/1)
Fans	2
Total Amps (int'l)	5.3 (3.4)
10 ft. Cord/Plug [attached] (int'l)	Yes (No)

### **SHIPPING DATA**

Weight (lbs.)	350 (159 kg)
Height - Crated (in.)	43 3/4 (1111 mm)
Width - Crated (in.)	45 (1143 mm)
Depth - Crated (in.)	47 (1194 mm)

<sup>\*</sup> Rating @ +25°F evaporator, 90°F ambient

Figures in parentheses reflect metric equivalents rounded to the nearest whole unit.

Refrigerator



Equipped with one NEMA-5-15P Plug (varies by country)

**Toll-Free: 800-523-7138** Phone: 215-244-1400 Fax: 215-244-9579

539 Dunksferry Road Bensalem, PA 19020 www.continentalrefrigerator.com

Due to our continued efforts in developing innovative products, specifications subject to change without notice.







© Copyright 2014. Continental Refrigerator. A Division of National Refrigeration & Air Conditioning Products, Inc.

### **Model Plan Views**





