# BASE MODEL SANDWICH UNIT

## Model: CRA93-18

## 93" Standard Top Sandwich Unit Refrigerator with Solid Doors - 18 Pans

Heavy gauge #300 Series stainless steel top, stainless steel front and end panels, galvanized steel rear and grill and aluminum interior. Certified under NSF-7 to maintain temperatures in 86°F ambient and designed to maintain NSF-7 temperatures in 100°F ambient.



## **Options and Accessories**

(upcharge and lead times may apply)		
Drawers in lieu of doors	Stainless steel pan slides	
Drawer section above the condensing unit*	Expansion valve system	
Overshelves (single or double)	Stainless steel shelves	
Condensing unit left or right	Flat insulated night covers	
Additional epoxy-coated steel shelves	Remote models	
Automatic, electric condensate evaporator	Door/drawer locks	
Exterior dial or digital thermometer	Adjustable legs	
Rear-mounted cutting board	Crumb catcher	
Stainless steel back and interior	Front breathing	

\*Drawer section above condensing unit holds (1) 12 x 20 x 6 pan



**Toll-Free: 800-523-7138** Phone: 215-244-1400 Fax: 215-244-9579

539 Dunksferry Road Bensalem, PA 19020 www.continentalrefrigerator.com

Project Name:	
Model Specified:	
Location:	
Item No:	Quantity:
	-
AIA #:	SIS #:

## **Standard Model Features**

### **REFRIGERATION SYSTEM**

Performance-rated refrigeration system
Environmentally-safe R-134a refrigerant
Unique air flow distribution allows pan product to maintain 33° - 41°F
Automatic, energy saving, non-electric condensate evaporator
Non-corrosive, plasticized fin evaporator coil
Easily serviceable, slide-out condensing unit

## **CABINET ARCHITECTURE**

2" non-CFC polyurethane foam insulation
Spring loaded, self closing doors
Magnetic snap-in door gaskets
Heavy-duty, epoxy-coated steel shelves
12" deep, full length nylon cutting board
Insulated lids
5" casters
Completely enclosed, vented and removable rear and side grills
Refrigerated door section above the condensing unit

### **MODEL FEATURES**

(18) 1/6 size non-recessed pans, 4" deep

Interior hanging thermometer

Field rehingeable doors

<u>NOTE</u>: CRA models come standard with a door over the condensing unit. A drawer over the condensing unit is an option.


**APPROVAL:** 


### **Model Specifications**


DIMENSIONAL DATA	
Net Capacity (cu. ft.)	32 (906 cu l)
1/6 Size Pans (4" deep)	18
Width, Overall (in.)	93 (2362 mm)
Depth, Overall (in.) (incl. handles & bumpers)	36 1/16 (916 mm)
Depth, Cutting Board (in.)	12 (305 mm)
Height, Overall (in.) (incl. 5" casters)	42 (1067 mm)
Shelf Area (sq. ft.)	14.2 (1.3 sq m)
No. of Shelves	6
No. of Full Doors	3
No. of Half Doors	1
Interior Depth (in.)	30 (762 mm)
Interior Height (in.)	26 (660 mm)
Interior Height (in.) (above condenser)	12 1/2 (318 mm)
Interior Width (in.)	89 (2261 mm)
REFRIGERANT DATA	
Condensing Unit Size (H.P.)	1/2
Capacity (BTU/Hr)*	4220
ELECTRICAL DATA	
Voltage (int'l)	115/60/1 (220/50/1)
Fans	4
Total Amps (int'l)	13.0 (8.4)
10 ft. Cord/Plug [attached] (int'l)	Yes (No)
SHIPPING DATA	
Weight (lbs.)	605 (274 kg)
Height - Crated (in.)	43 3/4 (1111 mm)
Width - Crated (in.)	95 (2413 mm)

47 (1194 mm)

**Model Plan Views** 







© Copyright 2014. Continental Refrigerator. A Division of National Refrigeration & Air Conditioning Products, Inc.

Depth - Crated (in.)

whole unit.

\* Rating @ +25°F evaporator, 90°F ambient

Equipped with one NEMA-5-15P Plug (varies by country)

Figures in parentheses reflect metric equivalents rounded to the nearest