SANDWICH UNIT REFRIGERATOR

Model: SW27-8C-FB-D

27" Cutting Top Sandwich Unit Refrigerator with Drawers - 8 Pans Front Breathing

Stainless steel front and top, aluminum end panels, case back and interior. Certified under NSF-7 to maintain temperatures in 86°F ambient and designed to maintain NSF-7 temperatures in 100°F ambient.



Options and Accessories

(upcharge and lead times may apply)

Stainless steel exterior and interior - SS models	Solid door in lieu of drawers
Stainless steel end panels - SA models	Expansion valve system
Glass door in lieu of drawers - GD models	Rear-mounted cutting board
Stainless steel finished back in lieu of aluminum	Flat insulated night cover
Overshelves (single or double)	Remote models
Automatic, electric condensate evaporator	Drawer locks
Three tier drawers	

Consult factory for other model configurations, options and accessories.

Project Name:	
Model Specified:	
Location:	

AIA #: SIS #:

Quantity:

Standard Model Features

REFRIGERATION SYSTEM

Item No:

Performance-rated refrigeration system

Environmentally-safe R-134a refrigerant

Unique air flow distribution allows pan product to maintain 33° - 41°F

Automatic, energy saving, non-electric condensate evaporator

Non-corrosive, plasticized fin evaporator coil

Easily serviceable, back mounted compressor

CABINET ARCHITECTURE

2" non-CFC polyurethane foam insulation

Magnetic snap-in drawer gaskets

19" deep, full length nylon cutting board

Stainless steel roll-out drawers

Insulated lid

3 5/8" casters

Completely enclosed, vented and removable case back

MODEL FEATURES

(8) 1/6 size non-recessed pans, 4" deep Interior hanging thermometer

Front breathers are a unique, field assembled, bottom mounted ventilation system designed to allow cabinets to be flush against a wall or built into a counter to conserve space.



Toll-Free: 800-523-7138 Phone: 215-244-1400 Fax: 215-244-9579

539 Dunksferry Road Bensalem, PA 19020 www.continentalrefrigerator.com

APPROVAL:

Model Specifications

DIMENSIONAL DATA	
Net Capacity (cu. ft.)	7.4 (210 cu I)
1/6 Size Pans (4" deep)	8
Width, Overall (in.)	27 1/2 (699 mm)
Depth, Overall (in.)	20.1/4 (070 mm)

38 1/4 (972 mm) (incl. cutting board & bumpers) Depth, Body Only

27 1/2 (699 mm) (less drawers) (in.) Depth, Cutting Board (in.) 19 (305 mm)

Height, Overall (in.) 40 7/8 (1038 mm) (incl. 3 5/8" casters) No. of Drawers (two tier) 2

3

REFRIGERANT DATA

No. of Drawers (three tier)

Condensing Unit Size (H.P.) 1/5 Capacity (BTU/Hr)* 1620

ELECTRICAL DATA

Voltage (int'l) 115/60/1 (220/50/1) Fans Total Amps (int'l) 6.3(3.7)10 ft. Cord/Plug [attached] (int'l) Yes (No)

SHIPPING DATA

Weight (lbs.)	180 (82 kg)
Height - Crated (in.)	43 1/4 (1099 mm)
Width - Crated (in.)	35 3/4 (908 mm)
Depth - Crated (in.)	46 (1168 mm)

DRAWER PAN CONFIGURATIONS

Two Tier: (1) 12 x 20 x 6 pan per drawer

Three Tier: (1) 12 x 20 x 4 pan per drawer

* Rating @ +25°F evaporator, 90°F ambient

Figures in parentheses reflect metric equivalents rounded to the nearest whole unit.

Refrigerator



Equipped with one NEMA-5-15P Plug (varies by country)

Toll-Free: 800-523-7138 Phone: 215-244-1400 Fax: 215-244-9579

539 Dunksferry Road Bensalem, PA 19020 www.continentalrefrigerator.com

Due to our continued efforts in developing innovative products, specifications subject to change without notice.







 $\hfill \ensuremath{\text{\bigcirc}}$ Copyright 2013. Continental Refrigerator. A Division of National Refrigeration & Air Conditioning Products, Inc.

Model Plan Views





