WORKTOP REFRIGERATOR

Model: SW27-GD

27" Worktop Display Refrigerator with Hinged Glass Door

Stainless steel front and top, aluminum end panels, case back and interior.

Designed to maintain NSF-7 temperatures in 100°F ambient.



Options and Accessories

(upcharge and lead times may apply)

| Stainless steel exterior and interior | Solid door |
|---|---|
| Stainless back in lieu of aluminum | Expansion valve system |
| Overshelves (single or double) | Adjustable legs |
| Additional epoxy-coated steel shelves | Remote models |
| Stainless steel shelves | Door lock |
| Automatic electric condensate evaporator | Digital thermometer |
| Stainless steel roll-out drawers in lieu of door - D models | Stacking collar |
| Backsplash - BS models | Special electrical requirements (consult factory) |

Consult factory for other model configurations, options and accessories.



Toll-Free: 800-523-7138 Phone: 215-244-1400 Fax: 215-244-9579

539 Dunksferry Road Bensalem, PA 19020 www.continentalrefrigerator.com

| _ | | | | | | | | | |
|---|----|---|---|----|----|---|---|---|---|
| μ | ro | П | ۵ | ct | N | 2 | m | Δ | ۰ |
| | ıυ | ľ | G | υı | 1. | u | ш | u | |

Model Specified:

Location:

Item No: Quantity:

AIA #: SIS #:

Standard Model Features

REFRIGERATION SYSTEM

Performance-rated refrigeration system

Environmentally-safe R-134a refrigerant

Automatic, energy saving, non-electric condensate evaporator

Non-corrosive, plasticized fin evaporator coil

Easily serviceable, back mounted compressor

CABINET ARCHITECTURE

2" non-CFC polyurethane foam insulation

Double pane, low-e, tempered hinged glass door

Magnetic snap-in door gasket

Heavy-duty, epoxy-coated steel shelf

Completely enclosed, vented and removable case back

5" casters

MODEL FEATURES

Interior hanging thermometer

LED interior lighting

Field rehingeable door

APPROVAL:

Model Specifications

| DIMENSIONAL DATA | |
|--|------------------|
| Net Capacity (cu. ft.) | 7.4 (210 cu I) |
| Width, Overall (in.) | 27 1/2 (699 mm) |
| Depth, Overall (in.) (incl. handle & bumpers) | 31 7/16 (799 mm) |
| Depth, Body Only (less door) (in.) | 27 1/2 (699 mm) |
| Height, Overall (in.) (incl. 5" casters) | 35 1/4 (895 mm) |
| Shelf Area (sq. ft.) | 3.5 (.3 sq m) |
| No. of Shelves | 1 |
| No. of Doors | 1 |
| Interior Depth (in.) | See Drawing |
| Interior Height (in.) | 26 1/4 (667 mm) |
| Interior Width (in.) | 24 1/2 (622 mm) |
| DEEDIGEDANT DATA | |

REFRIGERANT DATA

| Condensing Unit Size (H.P.) | 1/5 | |
|-----------------------------|------|--|
| Capacity (BTU/Hr)* | 1620 | |

ELECTRICAL DATA

| Voltage (int'l) | 115/60/1 (220/50/1) |
|-------------------------------------|---------------------|
| Fans | 2 |
| Total Amps (int'l) | 7.0 (3.7) |
| 10 ft. Cord/Plug [attached] (int'l) | Yes (No) |

SHIPPING DATA

| Weight (lbs.) | 180 (82 kg) |
|-----------------------|------------------|
| Height - Crated (in.) | 43 1/4 (1099 mm) |
| Width - Crated (in.) | 35 3/4 (908 mm) |
| Depth - Crated (in.) | 37 1/4 (946 mm) |

* Rating @ +25°F evaporator, 90°F ambient Figures in parentheses reflect metric equivalents rounded to the nearest whole unit.



Equipped with one NEMA-5-15P Plug (varies by country)



Toll-Free: 800-523-7138 Phone: 215-244-1400 Fax: 215-244-9579

539 Dunksferry Road Bensalem, PA 19020 www.continentalrefrigerator.com

Due to our continued efforts in developing innovative products, specifications subject to change without notice.









© Copyright 2013. Continental Refrigerator. A Division of National Refrigeration & Air Conditioning Products, Inc.

Model Plan Views



