## WORKTOP FREEZER (0°F)

## Model: SWF48-BS

# 48" Worktop Freezer with Solid Doors and 6" Backsplash

Stainless steel front and top, aluminum end panels, case back and interior.

Designed to maintain NSF-7 temperatures in 100°F ambient.



#### **Options and Accessories**

(upcharge and lead times may apply)		
Stainless steel exterior and interior	Expansion valve system	
Stainless back in lieu of aluminum	Adjustable legs	
Overshelves (single or double)	Remote models	
Additional epoxy-coated steel shelves	Door locks	
Stainless steel shelves	Digital thermometer	
Automatic electric condensate evaporator	Special electrical requirements (consult factory)	
Stainless steel roll-out drawers in lieu of doors - D models		

Consult factory for other model configurations, options and accessories.



**Toll-Free: 800-523-7138** Phone: 215-244-1400 Fax: 215-244-9579

539 Dunksferry Road Bensalem, PA 19020 www.continentalrefrigerator.com

Project Name:	
Model Specified:	
Location:	
Item No:	Quantity:
AIA #:	SIS #:

### **Standard Model Features**

#### **REFRIGERATION SYSTEM**

Performance-rated refrigeration system
Environmentally-safe R-404A refrigerant
Automatic, energy saving, non-electric condensate evaporator
Non-corrosive, plasticized fin evaporator coil
Easily serviceable, back mounted compressor

#### **CABINET ARCHITECTURE**

2" non-CFC polyurethane foam insulation Spring loaded, self closing doors Magnetic snap-in door gaskets Heavy-duty, epoxy-coated steel shelves Completely enclosed, vented and removable case back 5" casters

#### **MODEL FEATURES**

Interior hanging thermometer Field rehingeable doors Automatic electric defrost


**APPROVAL:** 

#### **Model Specifications**

#### **Model Plan Views**

DIMENSIONAL DATA	
Net Capacity (cu. ft.)	13.4 (379 cu l)
Width, Overall (in.)	48 (1219 mm)
Depth, Overall (in.) (incl. handles & bumpers)	31 7/16 (799 mm)
Depth, Body Only (less doors) (in.)	27 1/2 (699 mm)
Height, Overall (in.) (incl. 5" casters)	40 3/4 (1035 mm)
Shelf Area (sq. ft.)	6.8 (.6 sq m)
No. of Shelves	2
No. of Doors	2
Interior Depth (in.)	See Drawing
Interior Height (in.)	26 1/4 (667 mm)
Interior Width (in.)	44 (1118 mm)
REFRIGERANT DATA	
Condensing Unit Size (H.P.)	1/2
Capacity (BTU/Hr)*	2180
ELECTRICAL DATA	
Voltage (int'l)	115/60/1 (220/50/1)
Fans	2
Total Amps (int'l)	9.9 (3.5)
Defrost Amps (int'l)	5.0 (2.5)
10 ft. Cord/Plug [attached] (int'l)	Yes (No)
SHIPPING DATA	
Weight (lbs.)	258 (117 kg)
Height - Crated (in.)	43 1/4 (1099 mm)
Width - Crated (in.)	55 (1397 mm)
Depth - Crated (in.)	37 1/4 (946 mm)
* Rating @ -15°F evaporator, 90°F ambient	in rounded to the percent

Figures in parentheses reflect metric equivalents rounded to the nearest whole unit.





#### **Toll-Free: 800-523-7138** Phone: 215-244-1400 Fax: 215-244-9579

539 Dunksferry Road Bensalem, PA 19020 www.continentalrefrigerator.com

Due to our continued efforts in developing innovative products, specifications subject to change without notice.





© Copyright 2013. Continental Refrigerator. A Division of National Refrigeration & Air Conditioning Products, Inc.

