

PROJECT NAME: _____

LOCATION: _____


SPECIFIER ITEM NO. _____ **QTY:** _____

ENCORE PART NO. _____

Encore[®] 8" Deck Mount Faucet with Rigid Gooseneck Spout & Lever Handles

KL61-8x0x-RE1 Series

- KL61-8100-RE1 3" Spout, Ceramic Valves
- KL61-8000-RE1 3" Spout, Compression Valves
- KL61-8102-RE1 6" Spout, Ceramic Valves
- KL61-8002-RE1 6" Spout, Compression Valves
- KL61-8101-RE1 8" Spout, Ceramic Valves
- KL61-8001-RE1 8" Spout, Compression Valves



Dimensions shown in inches (mm) are for reference only and are subject to change.

1-1/8" (29mm) holes for deck are recommended to accommodate 1/2" supply nipples.

1/2" NPSM Male Inlets

Operating Temperature: 40-180°F (5-83°C)

Operating Pressure: 15-125psi

Approximate shipping weight - 5 lbs

Warranty - 2 years parts

Solid heavy duty cast body is specification and commercial quality

Commercial Quality Features

- Rigid gooseneck spout design
- ADA-compliant lever handles
- Built-in check valve to prevent cross-flow and back-flow
- Stainless steel spout

SANIGUARD[®] Product Protection

- Permanently incorporated on all touch points of Encore plumbing fixtures
- Inorganic, silver ion technology inhibits growth of common bacteria, yeasts, mold and fungi, minimizes cross-contamination

SPECIFICATIONS:

8" Deck Mount Faucet to be Encore KL61 Series in the following configuration:

- _____ KL61-8100-RE1 3" Spout, Ceramic Valves
- _____ KL61-8000-RE1 3" Spout, Compression Valves
- _____ KL61-8102-RE1 6" Spout, Ceramic Valves
- _____ KL61-8002-RE1 6" Spout, Compression Valves
- _____ KL61-8101-RE1 8" Spout, Ceramic Valves
- _____ KL61-8001-RE1 8" Spout, Compression Valves

Faucet body to be constructed of polished chrome plated brass with total lead content less than 0.25% by weighted average. Faucet to have 8" adjustable inlet centers and lever handles. Handles to be incorporated with SANIGUARD treatment. Color coded temperature indexes shall meet international standards. Valve to be 1/4-turn with integral check valve to prevent cross-flow and back-flow. Spout to be stainless steel rigid gooseneck style. 2.2gpm aerator @ 60psi standard with full flow stream bubbler screen spout tip.

Model No.	A	B	C
KL61-8100-RE1	3-1/2" (89mm)	8-9/16" (217mm)	10-13/16" (275mm)
KL61-8000-RE1	3-1/2" (89mm)	8-9/16" (217mm)	10-13/16" (275mm)
KL61-8102-RE1	6" (152mm)	8-1/16" (205mm)	11-3/4" (298mm)
KL61-8002-RE1	6" (152mm)	8-1/16" (205mm)	11-3/4" (298mm)
KL61-8101-RE1	8-1/2" (216mm)	8-13/16" (224mm)	14-9/16" (370mm)
KL61-8001-RE1	8-1/2" (216mm)	8-13/16" (224mm)	14-9/16" (370mm)

COMPLIES WITH:
 THE FEDERAL "REDUCTION OF LEAD IN DRINKING WATER ACT" -
 2011 - US SENATE BILL NO. S.3874
 NSF/ANSI 61/9, ANNEX G

