

1890 Swarthmore Avenue, PO Box 2020, Lakewood, NJ 08701 Phone: 800-526-3694, 732-363-4700, Fax: 732-364-8110 www.encoreplumbing.com • www.componenthardware.com

PROJECT NAME:	
LOCATION:	
SPECIFIER ITEM NO	QTY:
ENCORE PART NO	

Encore® Deck Mount Utility Spray

KL63-2x00-xx Series

KL63-2000 Compression valve,

No vacuum breaker

KL63-2000-VB Compression valve,

With vacuum breaker

KL63-2100 Ceramic valve,


No vacuum breaker


KL63-2100-VB Ceramic valve,

With vacuum breaker



KL63-2000-VB Shown





Note: Add 1-1/16" to overall height for vacuum breaker.

Dimensions shown in inches (mm) are for reference only and are subject to change.

1-1/8" (29mm) hole is recommended to accommodate 1/2" supply nipple.

1/2" NPT female inlet

Operating Temperature: 40-180°F (5-83°C)

Operating Pressure: 15-125psi

Approximate shipping weight - 5 lbs Warranty - 2 years parts

Solid heavy duty cast body is specification and commercial quality

Commercial Quality Features

- Provided with 3.3gpm, 1.6gpm and 1.2gpm spray faces
- · ADA-compliant lever handles
- 72" flexible S/S hose with Kool Grip™ handle

SANIGUARD® Product Protection

- Permanently incorporated on all touch points of Encore plumbing fixtures
- Inorganic, silver ion technology inhibits growth of common bacteria, yeasts, mold and fungi, minimizes cross-contamination

SPECIFICATIONS:

Deck Mount Utility Spray to be Encore KL63-2000 Series in the following configuration:

KL63-2000
KL63-2000-VB
KL63-2100
KL63-2100
KL63-2100-VB
Compression valve, no vacuum breaker
Ceramic valve, no vacuum breaker
Ceramic valve, with vacuum breaker
Ceramic valve, with vacuum breaker

Faucet body to be constructed of polished chrome plated brass with total lead content less than 0.25% by weighted average. Hose to be 72" flexible stainless steel with Kool Grip™ handle. Hose to have Santoprene® reinforced inner hose. Hold open ring and hose wall hook to be included. Valve to be 1/4-turn with integral check valve to prevent cross-flow and back-flow. Lever handle and grip to be incorporated with SANIGUARD treatment.

COMPLIES WITH:
THE FEDERAL "REDUCTION OF LEAD
IN DRINKING WATER ACT" –
2011 – US SENATE BILL NO. S.3874
NSF/ANSI 61/9, ANNEX G







