




Panel Meter Probes

Cooper offers a variety of probes with specific lead configurations to fit any application in our Panel Meter Series. Probes are available for type K thermocouple or thermistor based meters. Whether you need a

replacement probe or want to run additional sensors, you can choose from a variety of probes specifically designed for panel meters.


Model 1035

Thermistor NPT probe with 1/8" NPT fitting with ring connectors for PM200A




Model 2015

Thermistor air and surface probe with pigtail leads for PM200A



Model 2020

Thermistor air and surface probe with pigtail leads for PM200A




Model 2020K

Thermocouple air and surface probe with pigtail leads for PM400K



Model 2025

Thermistor air and surface probe with ring connectors for PM200A



Model 6020

Thermistor flexible probe for the PM200A



Model 7040

Panel meter thermistor air probe with pigtail leads for PM200A



MODELS: 1035, 2015, 2020, 2020K, 2025, 6020, 7040

Specifications: 1035/2020

| | |
|-----------------------|--|
| Temperature Range | -100° to 300°F/-73° to 149°C |
| Max. Tip Temperature | 300°F/149°C |
| Max. Cord Temperature | 400°F/204°C |
| Response Time | 1035 - 12 seconds 2020 - 6 seconds |
| Probe Type | Thermistor |
| Shaft Length | 1035 - 2.5" 2020 - 4.75" |
| Cord Length | 1035 - 72" teflon straight cord 2020 - 42" teflon straight cord |

Specifications: 2020K

| | |
|-----------------------|-------------------------------|
| Temperature Range | -100° to 1000°F/-73° to 538°C |
| Max. Tip Temperature | 1000°F/538°C |
| Max. Cord Temperature | 900°F/482°C |
| Response Time | 30 seconds |
| Probe Type | Type K thermocouple |
| Shaft Length | 4.75" |
| Cord Length | 42" wire |

Specifications: 2015/2025/6020

| | |
|-----------------------|---|
| Temperature Range | -100° to 200°F/-73° to 93°C |
| Max. Tip Temperature | 200°F/93°C |
| Max. Cord Temperature | 200°F/93°C |
| Response Time | 2015/2025 - 20 seconds 6020 - 50 seconds |
| Probe Type | Thermistor |
| Shaft Length | 2015/2025 - 0.5" 6020 - 18" |
| Cord Length | 2015/2025 - 144" PVC straight cord 6020 - 120" PVC straight cord |

Specifications: 7040

| | |
|-----------------------|-----------------------------|
| Temperature Range | -100° to 200°F/-73° to 93°C |
| Max. Tip Temperature | 200°F/93°C |
| Max. Cord Temperature | 200°F/93°C |
| Response Time | 7040 - 20 seconds |
| Probe Type | Thermistor |
| Shaft Length | 7040 - 0.5" |
| Cord Length | 7040 - 4" PVC pigtail lead |