

# 93916-K Screen Print Kit

The 93916-K Screen Print Kit with AquaTuff™ 35200-K Waterproof Thermocouple Instrument, allows you to monitor precise ink temperatures when profiling dryers to ensure perfect prints every time!



14235  
Hard Carrying Case



35200-K  
AquaTuff™ Thermocouple  
Instrument



10830  
Spare Wires



50008-K  
Screen Print Donut Probe with 15' cord



## Specifications

### 35200-K

- Temperature Range: -100° to 999°F (-73° to 537°C)
- Accuracy: With factory calibration,  $\pm 0.5^\circ\text{F}$  ( $\pm 0.3^\circ\text{C}$ ) over entire range at ambient temperatures between 68° to 86°F (20° to 30°C)
- Ambient Temperature Limits: 32° to 122°F (0° to 50°C)
- Resolution: Tenth Degree 0.1° / 1° user selectable
- Large, easy-to-read LCD screen with backlight
- °F / °C selectable
- On / Off button
- Hold button will freeze current reading
- IPX7 Waterproof-rated
- Auto shut-off after 10 minutes of non-use, user selectable
- Factory calibration constants stored in non-volatile memory
- N.I.S.T. Traceability: We certify that this instrument has been calibrated to temperature and / or electrical standards traceable to the U.S. Department of Commerce National Institute of Standard and Technology

- No Calibration Required: Your AquaTuff™ is factory calibrated to N.I.S.T. traceable standards. Under normal operating conditions, it will not need to be recalibrated
- Battery Life: 1800 hours typical, two (2) AAA Alkaline batteries (included)
- Compliances: CE certified, NSF listed, WEEE marked, RoHs compliant
- Warranty: 5 years

### 50008-K

- Temperature Range: -40° to 400°F (-40° to 205°C)
- Max Tip / Cable Temperature: 400°F (205°C)
- Response Time: 1 second, in liquid
- Cable Material: Silicone outer jacket
- Warranty: 1 year



**Measuring Success Since 1885**

Cooper-Atkins Corporation • 800-835-5011 • 860-347-2256 • www.cooper-atkins.com