

## ANGLE LEDGE ROLL-IN REFRIGERATOR RACK 273-65-12/1818

### FEATURES AND BENEFITS:

- Durable utility rack designed to fit roll-in or pass through refrigerators, freezers, and warming cabinets; eliminates unnecessary product handling while maintaining proper temperature levels. Holds 18" x 26" trays and 12" x 20" pans.
- Fully welded framework of structural aluminum extrusions for rigidity and durability.
- Constructed of non-corrosive, Hi-Tensile aluminum for strength.
- Extruded angle ledge pan supports, welded in place, accommodate heavy loads. 18" x 26" tray bottom rests on angle ledges. 12" x 20" pan lip holds on angle ledges. See reverse side for capacity and pan spacing.
- Heavy duty 5" swivel casters, two with brakes. Provides mobility when fully loaded.



273-65-12/1818






### ACCESSORIES and OPTIONS (Available at extra cost):

- Vertical Bumpers
- Perimeter Bumper

See page G-36 for accessory details.





CRES COR MODEL NO.	PAN			DIM "A" WIDTH	DIM "B" DEPTH	DIM "C" HEIGHT	INSIDE DIMENSIONS			WEIGHT ACT.	
	CAP	SIZE					WIDTH	DEPTH	HEIGHT		
273-65-12/1818	18	18 x 26	IN	20-1/4	26-1/2	64-3/4	18-1/16	26	56-1/2	LBS	58
		460 x 660	MM	515	660	1645	460	660	1435	KG	26
	18	12 x 20 x 2-1/2	IN								
		305 x 508 x 64	MM								

When ordering bumpers, add 2" to overall dimensions.



Gold indicates our Best Rack with the best warranty in the industry. 3-Year Parts / 1-Year Labor with lifetime guarantee against rust & corrosion

ALL CONSTRUCTION IS WELDED AND FINISHED.

**RACK:**

- Side Frames: Formed 1" square tubular aluminum.
- Top, center and bottom supports: 1" square aluminum tubing; welded to side frames.
- Casters: 5" dia., swivel, polyurethane tires, 1-1/4 wide. Two casters equipped with brakes.
- Casters bolted to plates welded to bottom supports.

**PAN SLIDES:**

- Extruded angles, 1-1/4 x 3-1/4 x .102; welded to frames on 3" centers.

**SHORT FORM SPECIFICATIONS**

Cres Cor Utility Rack Model 273-65-12/1818. Tubular aluminum welded construction with angles welded. Capacity (18) 18" x 26" or 12" x 20" pans on 3" centers. 5" swivel polyurethane casters. 3-Year Parts / 1-Year Labor warranty. Lifetime guarantee against rust & corrosion. Provide the following accessories: \_\_\_\_\_ . NSF listed.