



# E8610V & E8612V HEAVY-DUTY ALUMINUM TRANSPORT CARTS

Non-Insulated Aluminum with Universal Slides

CARTER-HOFFMANN  
11  
FOOD SERVICE EQUIPMENT  
ALUMINUM UTILITY CABINETS



Model Number	Capacity		Number of Slide Pairs	Tray Capacity* on Centers of:			Overall Dimensions			Caster Diameter		Shipping Weight				
	18x26	12x20		1-1/2"	3"	4-1/2"	Height	Depth	Width	in	mm	lbs	kgs			
							in	mm	in	mm	in	mm				
<input type="checkbox"/> E8610V	1	2	10	20	15	10	59 1/2	1511	31	787	26	660	5	127	151	68
<input type="checkbox"/> E8612V	1	2	12	24	18	12	65 1/2	1664	31	787	26	660	5	127	162	73

\*Standard capacity at 4-1/2" centers, adjustable on 1-1/2" centers.

**CONSTRUCTION...**Straight line modular styling with all seams hemmed-in for added strength & durability. Heavy gauge aluminum construction is heli-arc welded to form solid unit.

**CABINET MATERIAL...**Entire cabinet constructed on .080" thick aluminum, completely heli-arc welded and reinforced in the center of the cabinet with 1/4" x 1" tie rods. 2" x 1" x 1/8" thick specially extruded aluminum vertical uprights and 1-3/8" x 1" x 1/8" thick horizontal top supports are heli-arc welded for rigidity and support.

**BASE FRAME...**Constructed of .125" thick aluminum with heavy duty full width bolster pads. Entire base frame, including bolster pads, are heli-arc welded.

**CASTERS...**5" diameter plate mounted casters. All swivel.

**DOOR...**Face mounted, full length door constructed of .080" thick aluminum reinforced with 1" thick square tube vertical reinforcement channel. All sides are hemmed and completely heli-arc welded.

**HINGES...**Heavy duty stainless steel butt-type hinges with 3/8" diameter fix pin. 270 degree door swing.

**TRAY SLIDES...**Heavy duty universal type trays slides constructed of .125" thick aluminum. Fully adjustable at 1-1/2" centers with top, middle and bottom slides welded to uprights for additional support. Holds two 12"x20" pans or one 18"x26" tray per slide. Will also accommodate Gastronorm 2/1 pans (one per slide), 1/1 pans (2 per slide), and 20"x20" glass racks.

**LATCH...**Side mounted 12 gauge stainless steel door latch with 3/8" diameter pin for positive door closure.

**ACCESSORIES/OPTIONS...**

- Full perimeter bumper
- Polyurethane tread casters
- Floor lock
- 3-sided top rail
- Top mounted transport latch with padlock hasp
- Additional slide pairs

# SPECIFICATIONS

Specifications subject to change through product improvement & innovation.

**CARTER-HOFFMANN**  
1551 McCormick Ave., Mundelein, IL 60060  
(847) 362-5500 • (800) 323-9793 • Fax (847) 367-8981  
[www.carter-hoffmann.com](http://www.carter-hoffmann.com)

Printed in U.S.A. J20 0609  
Carter-Hoffmann is a trademark  
of Carter-Hoffmann LLC