




TE1S16 & TE1S20 ENCLOSED MOBILE TRAY CARTS


(Two trays per slide)




TE1S20




TE1S16
Side View



TE1S16
Top View



TE1S20
Side View



TE1S20
Top View

Carter-Hoffmann C.A.D. Drawing Scale: 1/4" = 1'

| Model Number | Tray Capacity* | Inside Working Height in mm | Overall Dimensions | | | | | | Caster Diameter in mm | Shipping Weight lbs kgs | |
|--------------|---|---|--------------------|------------|------------|----------|------------|--|---------------------------------|-----------------------------------|--|
| | 14" x 18" or 15" x 20" Trays at 5/8" Spacing | | Height | | Depth | | Width | | | | |
| | | | in mm | in mm | in mm | in mm | | | | | |
| TE1S16 | 16 | 43 1092 | 53 1346 | 38½ 978 | 29½ 749 | 6 152 | 250 114 | | | | |
| TE1S20 | 20 | 53½ 1359 | 63½ 1613 | 38½ 978 | 29½ 749 | 6 152 | 261 119 | | | | |

* Please specify tray size.

CONSTRUCTION...Welded cabinet construction. Cabinet formed and welded to base. All seams turned in to eliminate raw edges.

CABINET MATERIALS...Nickel-bearing type 300 series stainless steel; 18 gauge polished exterior walls.

BASE FRAME...12 gauge stainless steel full depth bolsters with 1" x 1" stainless steel perimeter channel supports.

CASTERS...6" diameter, institutional grade caster with polyurethane tread. Sealed roller bearing and double ball bearing swivel with Zerk grease fittings. Plate mounted and bolted to base in offset wheel ahead pattern.

BUMPER...Non-marking gray vinyl bumper set in heavy-duty 3/16" extruded aluminum frame with reinforced corner "cut outs."

DOORS...Double panel welded stainless steel doors. Cavity filled with high density fiberglass insulation. Decorative vinyl feature stripe.

LATCHES...Flush mounted heavy duty slide latch for positive closing of doors.

HINGES...Concealed, all stainless steel hinges permit 270 degree door operation.

HANDLES...Recessed handle grips mounted at swivel end of cabinet.

TRAY RACK ASSEMBLIES...Complete assemblies are removable without tools and constructed of 18 gauge stainless steel.

TRAY SLIDES...Two 14" x 18" or two 15" x 20" trays per slide. (Specify exact tray required.) Maximum inside working depth is 31 1/4" (794 mm).

OPTIONAL ACCESSORIES...

- ☐ Cart Wash Package
- ☐ Polyurethane Tread Casters
- ☐ Semi-Pneumatic Casters
- ☐ Full-Pneumatic Casters
- ☐ Wheel Brakes
- ☐ Drain and Plug
- ☐ Extra Stainless Steel Push Handle
- ☐ 3 or 4 Sided Top Rail
- ☐ Menu Card Holder
- ☐ Top Mounted Transport Latch

SPECIFICATIONS

CARTER-HOFFMANN
11 FOOD SERVICE EQUIPMENT
HEATED SERVERS

Printed in U.S.A. L5 0599
The name Carter-Hoffmann is a registered trade name of Carter-Hoffmann Corp.

Specifications subject to change through product improvement & innovation.

CARTER-HOFFMANN CORP.

1551 McCormick Ave., Mundelein, IL 60060

Tel (847) 362-5500 • (800) 323-9793 • Fax (847) 367-8981

www.carter-hoffmann.com

