



Description: **STANDARD PVC**

PRODUCT SPECIFICATIONS
SAVE-T PVC STRIP & SHEET

| Roll Size | | |
|----------------------------------|--|-------------|
| THICKNESS: | .040" to .250" | |
| WIDTH: | 4" to 60" | |
| Material Description | | |
| FINISH: | Double Polished | |
| COLOR: | Clear | |
| Physical Properties | | |
| Property | Result | ASTM |
| Hardness (15 sec. delay) | 79 A Scale | D2240 |
| Tensile Strength: | 2400 PSI | D412 |
| Ultimate Elongation: | 350% | D412 |
| Graves Tear: | 440 | D1004 |
| 100% Modulus: | 1400 PSI | D412 |
| Stiffness: (-20°F) | 44,000 PSI | - |
| Brittleness Temp: | -33° F | D746 |
| Operating Temp: | 0° F to 150° F | - |
| Specific Gravity: | 1.21 | D792 |
| Density: | 75 lbs. cu.ft. | C-177 |
| Thermal Conductivity (K): | .73 | C-177 |
| Thermal Resistance (R): | 1.37 | C-177 |
| Water Absorption: | | |
| UV Resistance: | YES | |
| Flammability Rating: | Compliant w/ California State Fire Marshal | |
| Shipped in a box on 6" cores | | |

Note: The information contained herein is believed to be reliable but no representations, guarantees or warranties of any kind are made as to its accuracy or suitability for particular applications.

TMI, LLC
5350 Campbells Run Road
Pittsburgh, PA 15205-9738
Web-Site: www.tmivinylsolutions.com

Toll Free: 800-888-9750
Phone: 412-787-9750
Fax: 412-787-3665
E-mail: vinylsolutions@tmi-pvc.com