



# Glass Door Merchandisers

## Sliding Glass Door Coolers

Project \_\_\_\_\_

Item \_\_\_\_\_

Quantity \_\_\_\_\_

CSI Section 11400

Approved \_\_\_\_\_

Date \_\_\_\_\_

### Models

- DMER33-SLG - 33ft<sup>3</sup> capacity sliding glass door cooler
- DMER45-SLG - 45ft<sup>3</sup> capacity sliding glass door cooler
- DMER67-SLG - 67ft<sup>3</sup> capacity sliding glass door cooler



DMER67-SLG

### Standard Features

- Blue top header sign standard
- Forced air evaporator for quick temperature pull down
- Attractive PVC frame
- Unit sits upon adjustable levelers
- Double paned Low-e glass door
- Four heavy duty shelves per section
- Built in door handle
- Robust body with 2-1/4" thick walls, injected with CFC-free polyurethane
- Exterior cabinet made of galvanized, pre-painted steel, with baked polyester paint
- Listed to NSF-7 for the storage and/or display of packaged or bottled product
- Heavy duty condensing unit for R134a, located in front for easy-access maintenance
- Forced-air condenser made of copper and aluminum, resistant to rust and saline environments
- Reinforced 16-gauge steel base
- One year parts and labor warranty and an additional four year compressor warranty (U.S.A./Canada only)

### Options & Accessories

- Wire shelf kit

### Specifications

**The exterior** is constructed of galvanized, pre-painted steel, with a baked polyester paint. The base is reinforced 16-gauge steel.

**The interior** is an attractive, NSF approved, white interior cabinet. It's robust body is constructed of 2-1/4" thick walls. The entire cabinet structure is insulated with high-density foamed in place CFC-free polyurethane. Innovative LED interior lighting design is protected by safety shielding. Four adjustable heavy duty coated wire shelves are provided per section.

**Refrigeration System:** Forced air condenser is made of copper and aluminum, resistant to rust and saline solutions. The self-contained refrigeration system uses environmentally friendly (CFC-free) 134A refrigerant. It is located in the front of the unit for easy access. The refrigerant flow is controlled using a capillary tube. Forced air evaporator ensures quick temperature pull-down.

**Door:** Extruded frame door is constructed with Low-E, double pane thermal glass. They are the latest in energy efficient technology.



Glass Door Merchandisers: Sliding Glass Door Coolers



# Glass Door Merchandisers

Sliding Glass Door Coolers

Plan View DMER33-SLG: 39.63" (101cm) wide, 29.00" (74cm) high.

Plan View DMER45-SLG: 51.00" (130cm) wide, 29.00" (74cm) high.

Plan View DMER67-SLG: 73.19" (186cm) wide, 29.00" (74cm) high.

Elevation View DMER33-SLG: 39.63" (101cm) wide, 78.00" (198cm) high.

Elevation View DMER45-SLG: 51.00" (130cm) wide, 78.00" (198cm) high.

Elevation View DMER67-SLG: 73.19" (186cm) wide, 78.00" (198cm) high.

| Specifications |                    |      |      |               |           |                 |
|----------------|--------------------|------|------|---------------|-----------|-----------------|
| Model          | Capacity           | H.P. | Amps | Voltage       | NEMA Plug | Shipping Weight |
| DMER33-SLG     | 33 ft <sup>3</sup> | 1/3  | 7.3  | 115V/60Hz/1Ph | 5-15P     | 425lbs/193kg    |
| DMER45-SLG     | 45 ft <sup>3</sup> | 1/2  | 10.7 | 115V/60Hz/1Ph | 5-15P     | 443lbs/201kg    |
| DMER67-SLG     | 67 ft <sup>3</sup> | 3/4  | 16.0 | 115V/60Hz/1Ph | 5-20P     | 661lbs/300kg    |

Delfield reserves the right to make changes to the design or specifications without prior notice.