

MOBILE TRAY & SILVER DISPENSERS



Single Style

Application

These self-leveling mobile tray and silver dispensers are offered in two styles: Single stack with eight silverware holders, or double stack with sixteen silverware holders. Each stack holds 150 trays.

These self-leveling mobile tray and silver dispensers can be found in tray lines or any place your needs require.

Construction

The lifting mechanisms are constructed of type 304 stainless steel with all exposed parts having a No. 4 finish. The Mobile Tray and Silver Dispenser is equipped with self-lubricating delrin wheels and a full complement of stainless steel extension springs which can be easily disconnected to adjust the lifting rate.

A removable stainless steel carrier tray provides bottom support for trays being dispensed.

The base is fabricated from 18-gauge type 304 stainless steel and reinforced with 16-gauge stainless steel angles. The tubular frames are fabricated from stainless steel tubing and securely welded to stainless steel angles on underside of base. The tubular frames are reinforced by horizontal 3/8" diameter type 304 stainless steel rods welded to each vertical frame. Four 5" heavy-duty non-marking swivel casters (2 with brakes) are securely mounted to the base and a non-marking bumper is mounted at each corner.

Item Numbers

Single

- DXIDTS1S1418
- DXIDTS1S1520
- DXIDTS1S1622

Double

- DXIDTS2S1418
- DXIDTS2S1520
- DXIDTS2S1622

Standard Features

- Stainless steel construction including stainless steel extension springs for long lasting dependable service.
- Patented self-leveling mechanism lifts out for easy cleaning.
- Field adjustable to accommodate different weights.
- Top mounted silverware holder conveniently located above trays.
- Corner Bumpers
- Plastic Silverware Cylinders


Warranty

One year parts and labor.

DINEX[®]

Building 2, Suite 106
628 Hebron Avenue
Glastonbury, CT 06033
800.523.9752 Fax: 860.652.3135
www.dinex.com

MOBILE TRAY & SILVER DISPENSERS



Items and Dimensions

ITEM NUMBER	MODEL NUMBER	LENGTH	DEPTH	HEIGHT	NUMBER OF CYLINDERS	MAXIMUM TRAY SIZE	SHIP WEIGHT	SHIP CUBE
DXIDTS1S1418	IDTS1S/1418	23.19" (58.9cm)	28.38" (72.1cm)	53.75" (136.5cm)	8	14.375" x 18.75"	143 lb. (65.0kg)	13.6
DXIDTS1S1520	IDTS1S/1520	23.19" (58.9cm)	28.38" (72.1cm)	53.75" (136.5cm)	8	15.375" x 20.75"	143 lb. (65.0kg)	15.7
DXIDTS1S1622	IDTS1S/1622	23.19" (58.9cm)	28.38" (72.1cm)	53.75" (136.5cm)	8	16.375" x 22.75"	148 lb. (67.3kg)	17.9
DXIDTS2S1418	IDTS2S/1418	43.19" (109.7cm)	28.38" (72.1cm)	53.75" (136.5cm)	16	14.375" x 18.75"	162 lb. (73.5kg)	26.7
DXIDTS2S1520	IDTS2S/1520	43.19" (109.7cm)	28.38" (72.1cm)	53.75" (136.5cm)	16	15.375" x 20.75"	180 lb. (81.7kg)	30.7
DXIDTS2S1622	IDTS2S/1622	43.19" (109.7cm)	28.38" (72.1cm)	53.75" (136.5cm)	16	16.375" x 22.75"	184 lb. (83.5kg)	35.0



Please confirm that you have the most current specification sheet by visiting www.dinex.com.
 Dinex® reserves the right to change specifications and product design without notice.
 Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment.



Building 2, Suite 106
 628 Hebron Avenue
 Glastonbury, CT 06033
 800.523.9752 Fax: 860.652.3135
www.dinex.com